

SHOTGUN BIG DOT TRITIUM FRONT SIGHT - VENT RIB BIG DOT TRITIUM

[Shotgun Parts](#) > [Sights](#) > [Front Sights](#)

Installs Easily Over The Existing Bead Sight

SHOTGUN BIG DOT TRITIUM FRONT SIGHT Highly visible, tritium dot front sight surrounded by a large white ring epoxies over the existing front bead sight to help improve target focus and low light sight acquisition and sight recovery after muzzle flash. Installs over front sight beads from .125' - .140' diameter by filling the cavity on the underside of the sight with Brownells Acraglas Gel, then pressing the sight over the bead and allowing it to fully cure. If existing bead is too small or too large, replace with Brownells #6 bead for 3-56 threads or #26 for 6-48 threads. Some shotgun barrels may require drilling and tapping of existing hole to 6-48 for installation of #26 Brownells bead. Vent Rib model with flat bottom fits shotgun barrels with ventilated ribs. Plain Barrel model with cupped bottom fits round shotgun barrels. Includes instructions. SPECS: Machined steel, black, matte finish. Big Dot .161" (4mm) diameter. Fits beads from .125" (3.2mm) to .140" (3.5mm). Vent Rib fits ventilated ribs. Plain Barrel fits round barrels. Includes instructions.



Attributes

- Name: [VENT RIB BIG DOT TRITIUM](#)
- Manufacturer: [XS SIGHT SYSTEMS](#)
- Product no.: 006000159
- Mfr. No.: SG-2002-3
- Make: Remington
- Model: Universal Shotguns
- Sight Color: White
- Style: Tritium Beads
- Delivery weight: 0.045kg
- Shipping height: 33mm
- Shipping width: 122mm
- Shipping length: 185mm
- UPC: 647533025751

Item details

Made in USA

Table of Contents

- Startpage
- SHOTGUN BIG DOT TRITIUM FRONT SIGHT SAFETY INSTRUCTIONS
- About Us

SHOTGUN BIG DOT TRITIUM FRONT SIGHT SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the SHOTGUN BIG DOT TRITIUM FRONT SIGHT. This product is designed to enhance your shooting experience by providing a highly visible front sight for improved target focus, especially in lowlight conditions. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Product Safety:** This product is designed to meet safety standards for nonfood items. Ensure that you understand the instructions before use.
- Enhanced Recalls:** In the event of a safety issue or recall, updates will be provided through official channels. Please stay informed.
- Online Shopping:** If purchased online, ensure that the seller complies with safety regulations similar to those of physical stores.
- Special Consumer Focus:** Extra care should be taken when used by vulnerable groups, including children. Adult supervision is recommended.
- EU Contact Point:** For safety inquiries, please refer to the official EU safety contact points.
- Rapid Alerts:** Stay alert for any safety updates regarding this product via the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Installation Safety:** Ensure that the installation area is clean and free from obstructions.
- Bead Size Compatibility:** Verify that the existing front bead sight is compatible with the SHOTGUN BIG DOT TRITIUM FRONT SIGHT. If it is too small or too large, replace it with the appropriate Brownells bead.
- Use of Adhesives:** Use Brownells Acraglas Gel as directed for installation. Ensure proper ventilation when using adhesives.
- Muzzle Safety:** Always handle firearms safely. Keep the muzzle pointed in a safe direction during installation and use.
- Shooting Safety:** Wear appropriate eye and ear protection when shooting.
- Child Safety:** Keep firearms and accessories out of reach of children.

Instructions for Installation and Usage

1. Preparation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Clean the area around the existing front bead sight.

2. Installation:

- Fill the cavity on the underside of the SHOTGUN BIG DOT TRITIUM FRONT SIGHT with Brownells Acraglas Gel.
- Press the sight over the existing front bead sight.
- Allow the adhesive to fully cure as per the manufacturer's instructions.

3. Bead Replacement (if necessary):

- If the existing bead is not suitable, replace it with a Brownells #6 bead for 356 threads or a #26 bead for 648 threads.
- Some shotgun barrels may require drilling and tapping to accommodate the new bead.

4. Usage:

- After installation, practice aiming with the new sight in a safe environment.
- Ensure that you can clearly see the tritium dot and white ring against your target.

Disposal Instructions

- Dispose of any unused or expired adhesives and materials in accordance with local regulations.
- Do not dispose of the product in regular household waste. Check with local waste management for proper disposal methods.

Contact Information for Further Support

For any questions or further support regarding the SHOTGUN BIG DOT TRITIUM FRONT SIGHT, please refer to the manufacturer's contact points or check the official website for updates and additional resources.

By following these safety instructions, you can ensure a safe and enjoyable experience with your SHOTGUN BIG DOT TRITIUM FRONT SIGHT. Always prioritize safety and responsible firearm handling.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at