

FRONT SIGHT TOOL FOR GLOCK® - BROWNELLS FRONT SIGHT TOOL FOR GLOCKS

[Gunsmith Tools](#) > [Handgun Tools](#) > [Sight Tools](#)

Brownells front sight tool for Glocks fits the hex screw found on aftermarket front sights. Fits the opening found on longslide Glocks as well.



Attributes

- Name: [BROWNELLS FRONT SIGHT TOOL FOR GLOCKS](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 080001092
- Mfr. No.:
- Model: Universal Handguns
- Weapon type: Glock
- Delivery weight: 0.014kg
- Shipping height: 13mm
- Shipping width: 58mm
- Shipping length: 102mm
- UPC: 050806110700

Item details

Made in USA

Table of Contents

- Startpage
- FRONT SIGHT TOOL FOR GLOCK® Safety Instruction Guide
- About Us

FRONT SIGHT TOOL FOR GLOCK® Safety Instruction Guide

Introduction

Thank you for choosing the Brownells Front Sight Tool for Glocks. This tool is designed to assist in the installation and adjustment of front sights on Glock handguns. To ensure safe and effective use, please read this safety instruction guide carefully. Following these guidelines will help you avoid potential hazards and ensure compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Always use the tool as intended and according to the instructions provided.
- Keep the tool out of reach of children and vulnerable individuals.
- Inspect the tool before each use to ensure it is in good condition.
- Do not use the tool if it is damaged or malfunctioning.
- Report any unsafe conditions or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure you are wearing appropriate safety gear, such as safety glasses, when using the tool.
- Be aware of your surroundings and ensure no one is in the vicinity while using the tool.
- Avoid using excessive force when operating the tool to prevent damage to the firearm or injury to yourself.
- Always work in a welllit area to enhance visibility and accuracy during use.
- Do not attempt to modify the tool; alterations may lead to unsafe conditions.

Instructions for Installation and Usage

1. Preparation

- Ensure that the firearm is unloaded and safe to handle before beginning any work.
- Gather all necessary tools and materials, including the Brownells Front Sight Tool.

2. Installation of Front Sight

- Locate the hex screw on the aftermarket front sight of your Glock.
- Insert the Brownells Front Sight Tool into the hex screw opening.
- Turn the tool clockwise to tighten the sight or counterclockwise to loosen it. Use gentle pressure to avoid stripping the screw.

3. Adjustment of Front Sight

- If adjustments are needed after installation, repeat the above steps as necessary.
- Always check for proper alignment and secure fit after adjustments.

4. PostInstallation Check

- Once installation or adjustment is complete, perform a final inspection of the sight to ensure it is secure.
- Test the firearm in a safe environment to confirm the sight is functioning correctly.

Disposal Instructions

- Dispose of the tool responsibly at a designated waste facility.
- Do not throw the tool in regular household waste.
- Follow local regulations regarding the disposal of metal tools and equipment.

Contact Information for Further Support

For any inquiries or concerns regarding the Brownells Front Sight Tool for Glocks, please refer to the contact information provided in the product packaging or visit the manufacturer's website.

Conclusion

By following these safety instructions, you can ensure a safe and effective experience with the Brownells Front Sight Tool for Glocks. Thank you for prioritizing safety and compliance with the EU General Product Safety Regulation. Enjoy your enhanced shooting experience!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk