

SMITH & WESSON SIGHT NUT SPANNER - BROWNELLS S&W REAR SIGHT SPANNER 2 PACK

[Gunsmith Tools](#) > [Handgun Tools](#) > [Sight Tools](#)

Parts Required For S&W Factory Rear Sights

MAGNA-TIP® Bit, made to fit the windage nut that secures the S&W rear sight leaf. To use: Drill out staking, hold nut with Spanner and unscrew the screw. To install: Hold new nut with Spanner and seat screw. Always turn the screw; never the nut. Because it is fragile, and can break if you turn it, the Spanner is not guaranteed against breakage.



Attributes

- Name: [BROWNELLS S&W REAR SIGHT SPANNER 2 PACK](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 080431000
- Mfr. No.:
- Weapon type: Universal Handguns
- Delivery weight: 0.018kg
- Shipping height: 16mm
- Shipping width: 52mm
- Shipping length: 136mm
- UPC: 050806112070

Item details

Made in USA

Table of Contents

- Startpage
- SMITH & WESSON SIGHT NUT SPANNER SAFETY INSTRUCTIONS
- About Us

SMITH & WESSON SIGHT NUT SPANNER SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the SMITH & WESSON SIGHT NUT SPANNER. This product is designed to assist in the installation and removal of the rear sight nut on S&W firearms. Please read and follow these safety instructions carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Always use the product in accordance with the manufacturer's instructions.
- Ensure that the work area is clean and free of obstructions.
- Keep the product out of reach of children and vulnerable individuals.
- Inspect the Spanner for any damage before use. Do not use if damaged.
- Report any unsafe conditions or accidents to the appropriate authorities.
- Stay informed about product recalls and safety alerts through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Use the Spanner only for its intended purpose: to hold the rear sight nut while installing or removing screws.
- Always turn the screw, not the nut, to prevent damage to the Spanner or the nut.
- If the Spanner feels stuck or difficult to turn, stop using it and inspect for any obstructions or damage.
- Be cautious when drilling out staking; ensure proper eye protection is worn to avoid injury from metal shavings.
- Handle the Spanner with care, as it is fragile and can break if excessive force is applied.

Instructions for Installation and Usage

To Remove the Rear Sight Nut:

1. **Preparation:** Ensure the firearm is unloaded and safe to work on.
2. **Drill Out Staking:** Carefully drill out any staking material that may be securing the nut. Wear appropriate eye protection.
3. **Hold the Nut:** Use the Spanner to securely hold the windage nut.
4. **Unscrew the Screw:** Turn the screw counterclockwise to remove it. Always turn the screw, never the nut.

To Install the New Rear Sight Nut:

1. **Preparation:** Ensure the firearm is unloaded and safe to work on.
2. **Hold the New Nut:** Use the Spanner to hold the new windage nut in place.
3. **Seat the Screw:** Insert the screw and turn it clockwise to secure it. Always turn the screw, never the nut.

Disposal Instructions

- Dispose of the product according to local regulations regarding electronic and mechanical waste.
- Do not dispose of the product in regular household waste.

Contact Information for Further Support

For any questions or concerns regarding the SMITH & WESSON SIGHT NUT SPANNER, please refer to the manufacturer's contact information provided with your product packaging.

Thank you for your attention to these safety instructions. Your safety is our priority.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk