

# NYLON FRONT-SIGHT DRIFT PUNCHES - NYLON FRONT SIGHT DRIFT PUNCHES 5/16" DIAMETER 3-PACK

[Gunsmith Tools & Supplies](#) > [General Gunsmith Tools](#) > [Punches](#)

## Non-Marking Drift For Sights & Pins

**NYLON FRONT-SIGHT DRIFT PUNCHES** The Brownells Nylon Front-Sight Drift Punch is a specialized tool designed to facilitate the installation and removal of front sights on firearms without causing damage to the sight or barrel. Crafted from durable nylon, this punch ensures a mar-free experience during gunsmithing tasks. **Description and Features:** **Purpose-Built Design:** Specifically engineered to drive front sights in or out without marring the sight or barrel, addressing the limitations of brass and fiber punches. **Durable Nylon Construction:** Unlike brass punches that can leave marks or fiber punches that may shatter under impact, this nylon punch maintains its shape and integrity even after prolonged use. **Optimal Dimensions:** Measuring 4 inches in length and 5/16 inches in diameter, it offers a comfortable grip and precise control during sight adjustments. **Specifications:** **Material:** High-quality nylon **Length:** 4 inches (10.2 cm) **Diameter:** 5/16 inches (7.9 mm) **Customer Insights:** Our customers report that the Brownells Nylon Front-Sight Drift Punch is an essential tool for gunsmiths and firearm enthusiasts. Its durable nylon construction prevents marring of firearm surfaces, and its resilience under repeated use makes it a reliable choice for front sight adjustments. Incorporating the Brownells Nylon Front-Sight Drift Punch into your toolkit ensures you have a reliable, non-marring solution for front sight installation and removal, enhancing the quality and precision of your firearm maintenance tasks.



## Attributes

- Name: [NYLON FRONT SIGHT DRIFT PUNCHES 5/16" DIAMETER 3-PACK](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 080478000
- Mfr. No.:
- Material: Nylon
- Size: 5/16 in
- Style: Drift
- Quantity: 3
- Delivery weight: 0.023kg
- Shipping width: 83mm
- Shipping length: 146mm
- UPC: 050806009479

## Item details

Made in USA

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for Brownells Nylon FrontSight Drift Punches](#)
- [About Us](#)

# Safety Instruction Guide for Brownells Nylon FrontSight Drift Punches

## Introduction

Thank you for choosing the Brownells Nylon FrontSight Drift Punches. This guide provides essential safety instructions and usage information to ensure safe and effective operation. Please read this guide carefully before using the product.

## General Safety Guidelines

- Always use the Nylon FrontSight Drift Punches in accordance with the manufacturer's instructions.
- Inspect the tool before each use to ensure it is in good condition and free from defects.
- Keep the tool out of reach of children and vulnerable individuals.
- Do not use the punch for any purpose other than its intended use.
- Store the tool in a dry, safe place when not in use.
- Report any unsafe conditions or incidents to the relevant authorities.

## Specific Safety Precautions for Use

- Wear appropriate personal protective equipment (PPE), such as safety glasses, to protect your eyes from potential debris.
- Ensure that the firearm is unloaded and pointed in a safe direction before attempting to install or remove front sights.
- Use the Nylon FrontSight Drift Punch on a stable surface to maintain control during use.
- Avoid applying excessive force when using the punch to prevent damage to the sight or barrel.
- Do not use the punch if it shows signs of wear or damage.

## Instructions for Installation and Usage

### 1. Preparation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather necessary tools and materials, including the Nylon FrontSight Drift Punch and a suitable hammer.

### 2. Installation of Front Sight:

- Align the front sight with the mounting slot on the firearm.
- Position the Nylon FrontSight Drift Punch against the front sight.
- Gently tap the punch with a hammer to drive the sight into place. Use controlled strikes to avoid damaging the sight or barrel.

### 3. Removal of Front Sight:

- Position the Nylon FrontSight Drift Punch against the front sight.
- Gently tap the punch with a hammer to drive the sight out. Use controlled strikes to ensure a smooth removal process.

### 4. PostUse:

- Clean the tool after use to remove any debris or residue.
- Store the Nylon FrontSight Drift Punch in a safe place.

## **Disposal Instructions**

- Dispose of the Nylon FrontSight Drift Punch in accordance with local regulations.
- Do not dispose of the product in general household waste.
- Consider recycling options if available.

## **Contact Information for Further Support**

For any inquiries, please refer to the manufacturer's contact information provided with the product packaging or on the manufacturer's website.

By following these safety instructions, you can ensure a safe and effective experience with the Brownells Nylon FrontSight Drift Punches. Thank you for your attention to safety and responsible usage.

# About Us

## Brownells Austria

**Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

[www.brownells.at](http://www.brownells.at)