

FILLISTER 8-40 SIGHT SCREW COUNTERBORE

[Gunsmith Tools & Supplies](#) > [Sight & Scope Installation Tools](#) > [Sight Screw Head Counterbores](#)

High-Speed; For Popular Sight Screws; Made To Our Exact Spec For Most Sight Base Screws

Overall 2½" (6.3mm); Body Dia. .250" (6.3mm); Pilot Dia. .165" (4.2mm); Pilot Length 1/8" (3.2mm); 90° Shoulder. Use Drill No. 19 for Pilot Hole.



Attributes

- Name: [FILLISTER 8-40 SIGHT SCREW COUNTERBORE](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 080671841
- Mfr. No.: 88146
- Delivery weight: 0.014kg
- Shipping width: 83mm
- Shipping length: 146mm
- UPC: 050806017597

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [FILLISTER 840 SIGHT SCREW COUNTERBORE Safety Instruction Guide](#)
- [About Us](#)

FILLISTER 840 SIGHT SCREW COUNTERBORE

Safety Instruction Guide

Introduction

Thank you for choosing the FILLISTER 840 SIGHT SCREW COUNTERBORE. This product is designed to provide a reliable solution for counterboring sight screw holes. To ensure your safety and the safe use of this product, please read and follow the guidelines outlined in this instruction guide.

General Safety Guidelines

- Always read the instruction manual before using the product.
- Ensure that the work area is clean and welllit to prevent accidents.
- Use personal protective equipment (PPE) such as safety glasses and gloves.
- Keep the product out of reach of children and vulnerable individuals.
- Do not use the product for purposes other than those specified.
- Report any unsafe conditions or product defects to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure the drill is compatible with the FILLISTER 840 SIGHT SCREW COUNTERBORE before use.
- Always use the recommended Drill No. 19 for pilot holes to avoid damaging the tool or workpiece.
- Do not exceed the recommended pilot length of 1/8" (3.2mm) to prevent accidents.
- Inspect the tool for any damage or wear before each use.
- Avoid wearing loose clothing or jewelry that could become entangled in the tool during operation.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools and materials, including the FILLISTER 840 SIGHT SCREW COUNTERBORE and Drill No. 19.
- Ensure that you are working in a stable and secure environment.

2. Setting Up:

- Mark the desired location for the pilot hole on the workpiece.
- Secure the workpiece to prevent movement during drilling.

3. Drilling the Pilot Hole:

- Attach the FILLISTER 840 SIGHT SCREW COUNTERBORE to the drill.
- Align the tool with the marked spot and ensure it is perpendicular to the workpiece.
- Begin drilling at a slow speed, gradually increasing as needed. Maintain steady pressure without forcing the tool.
- Stop drilling when the pilot hole reaches the required depth of 1/8" (3.2mm).

4. Finishing Up:

- Remove the tool from the workpiece carefully.
- Clean the area of any debris or shavings to maintain a safe workspace.

Disposal Instructions

- Dispose of the FILLISTER 840 SIGHT SCREW COUNTERBORE responsibly, following local regulations for tool disposal.
- Do not dispose of the product in household waste. Check for recycling options in your area.

Contact Information for Further Support

For any inquiries regarding the FILLISTER 840 SIGHT SCREW COUNTERBORE, please refer to the manufacturer's contact information included in the product packaging or visit the manufacturer's website for additional resources.

Thank you for your attention to these safety instructions. Your safety is our priority, and following these guidelines will help ensure a safe and effective use of the FILLISTER 840 SIGHT SCREW COUNTERBORE.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at