

SLIM GRIP SCREWS, SS

[Handgun Parts](#) > [Grip Parts](#) > [Grip Screws](#)

Give Your 1911 Auto That High Tech Look

Allen head screws are contoured to fit flush in your 1911 slim grips. Screws are sold separately, in paks of 4.



Attributes

- Name: [SLIM GRIP SCREWS, SS](#)
- Manufacturer: [ED BROWN](#)
- Product no.: 087000059
- Mfr. No.: 804-SLIM
- Make: 1911
- Model: Officers,Government,Commander
- Quantity: 4
- Delivery weight: 0.045kg
- Shipping width: 83mm
- Shipping length: 146mm
- UPC: 800732803036

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [SLIM GRIP SCREWS Safety Instruction Guide](#)
- [About Us](#)

SLIM GRIP SCREWS Safety Instruction Guide

Introduction

Thank you for choosing SLIM GRIP SCREWS. These Allen head screws are specifically designed to fit flush in your 1911 slim grips. This guide provides essential safety instructions and usage guidelines to ensure safe and effective use of the product.

General Safety Guidelines

- Always ensure that your work area is clean and free from distractions before handling the screws.
- Keep the screws and any tools out of reach of children and pets to prevent accidents.
- Inspect the screws for any damage or wear before use. Do not use damaged screws.
- Use proper personal protective equipment (PPE) such as safety glasses when installing screws.
- Follow all local regulations and guidelines regarding firearm accessories and modifications.

Specific Safety Precautions for Use

- Ensure that the screws are compatible with your specific 1911 model (Government, Commander, Officers).
- Do not overtighten the screws, as this may damage the grips or the screws themselves.
- Always use the provided 3/32" Allen wrench for installation to avoid stripping the screw heads.
- If you experience resistance while installing, stop and check for misalignment before proceeding.
- Avoid using screws that show signs of corrosion or rust.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including the screws and the 3/32" Allen wrench.
- Ensure that the firearm is unloaded and safe to handle before beginning installation.

2. Installation:

- Align the screw hole in the grip with the corresponding hole in the frame of the firearm.
- Insert the screw into the hole and handtighten it until snug.
- Using the 3/32" Allen wrench, tighten the screw until secure, but do not overtighten.
- Repeat the process for all screws being installed.

3. PostInstallation:

- Doublecheck that all screws are securely fastened.
- Inspect the grips to ensure they are properly fitted and aligned.
- Test the firearm to ensure proper functioning after installation.

Disposal Instructions

- Dispose of any unused or damaged screws in accordance with local waste disposal regulations.
- Do not dispose of screws in a manner that could pose a risk to the environment or public safety.

Contact Information for Further Support

For any safety inquiries or concerns regarding the SLIM GRIP SCREWS, please refer to the EUbased contact point provided by the manufacturer or authorized distributor.

Conclusion

By following these safety instructions and guidelines, you can ensure the safe use and installation of your SLIM GRIP SCREWS. Always prioritize safety and adhere to local regulations when modifying or handling firearms. Thank you for your attention to these important safety measures.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at