

FRONT SIGHT TOOL for GLOCK® - FRONT SIGHT TOOL FOR GLOCK

[Gunsmith Tools & Supplies](#) > [Handgun Tools](#) > [Sight Tools](#)

Easily Removes/Installs Glock Front Sights

Fits the small, hex head screw that holds Glock aftermarket sights in place. Makes installing replacement sights or removing sights for maintenance easier with less chance of damage. Hex shank fits Magna-Tip® screwdrivers. Not for use with 6" slides.



Attributes

- Name: [FRONT SIGHT TOOL FOR GLOCK](#)
- Manufacturer: [ED BROWN](#)
- Product no.: 087017001
- Mfr. No.: 952
- Make: Glock
- Model: Universal Handguns
- Delivery weight: 0.014kg
- Shipping width: 83mm
- Shipping length: 146mm
- UPC: 800732952000

Item details

Made in USA

Table of Contents

- Startpage
- FRONT SIGHT TOOL for GLOCK® Safety Instruction Guide
- About Us

FRONT SIGHT TOOL for GLOCK® Safety Instruction Guide

Introduction

Thank you for purchasing the FRONT SIGHT TOOL for GLOCK®. This tool is designed to assist you in the installation and removal of aftermarket sights for your Glock handgun. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Always use the FRONT SIGHT TOOL in accordance with the manufacturer's instructions.
- Keep the tool out of reach of children and vulnerable individuals.
- Inspect the tool for any damage before use. Do not use if damaged.
- Use the tool in a welllit and clean environment to prevent accidents.
- Always wear appropriate safety gear, such as safety glasses, when using the tool.
- Be aware of your surroundings and ensure that no one is in the vicinity of the tool while in use.

Specific Safety Precautions for Use

- Ensure the firearm is unloaded before attempting to install or remove sights.
- Do not force the tool into screws; apply gentle pressure to avoid stripping the screw head.
- Do not use the FRONT SIGHT TOOL with 6" slides as it is not designed for that application.
- Use the tool only with MagnaTip® screwdrivers for proper fit and functionality.
- Avoid using excessive force when tightening or loosening screws to prevent damage to the sight or firearm.

Instructions for Installation and Usage

1. Preparation

- Ensure that the firearm is unloaded and pointed in a safe direction.
- Gather the necessary tools, including the FRONT SIGHT TOOL and a compatible MagnaTip® screwdriver.

2. Installing Replacement Sights

- Align the new sight with the mounting hole on the slide of the firearm.
- Insert the hex head screw into the sight and handtighten it to hold the sight in place.
- Use the FRONT SIGHT TOOL with the MagnaTip® screwdriver to tighten the screw securely, but do not overtighten.

3. Removing Sights for Maintenance

- Ensure the firearm is unloaded and pointed in a safe direction.
- Use the FRONT SIGHT TOOL with the MagnaTip® screwdriver to loosen the hex head screw.
- Carefully remove the screw and the sight from the firearm.

4. PostUse Care

- Clean the tool after use to maintain its functionality.
- Store the FRONT SIGHT TOOL in a safe and dry place, away from children and unauthorized users.

Disposal Instructions

- Dispose of the FRONT SIGHT TOOL in accordance with local regulations.
- If the tool is damaged beyond repair, consider recycling the metal components if possible.

Contact Information for Further Support

For safety inquiries or additional support regarding the FRONT SIGHT TOOL for GLOCK®, please contact the manufacturer or refer to the product packaging for further assistance.

By following these guidelines, you can ensure a safe and effective experience with your FRONT SIGHT TOOL for GLOCK®. Always prioritize safety and compliance with local regulations when using this product.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at