

MAX-50 SCOPE RINGS - 30MM MEDIUM ALUMINUM MAX-50 RINGS

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

The MAX-50 rings are one inch wide, giving them 60% more holding power than any other ring available from Badger Ordnance. Utilizing 6 #8-40 Torx screws to distribute the load providing the maximum amount of holding power while minimizing the chance of damaging the scope. Machined from Steel or Aluminum as serialized matched pairs. MIL STD 1913 compatible, designed for the demanding .50 BMG round.



Attributes

- Name: [30MM MEDIUM ALUMINUM MAX-50 RINGS](#)
- Manufacturer: [BADGER ORDNANCE](#)
- Product no.: 093000095
- Mfr. No.: 306-19
- Finish: Matte Black
- Height: .823"
- Material: Aluminum
- Scope Tube Diameter: 30mm
- Size: Standard
- Delivery weight: 0.175kg
- Shipping height: 51mm
- Shipping width: 51mm
- Shipping length: 76mm

Item details

Made in USA

Table of Contents

- Startpage
- MAX50 SCOPE RINGS Safety Instruction Guide
- About Us

MAX50 SCOPE RINGS Safety Instruction Guide

Introduction

Thank you for choosing the MAX50 SCOPE RINGS. This guide provides essential safety information and instructions to ensure the safe and effective use of this product. Please read this guide carefully before installation and usage.

General Safety Guidelines

- Ensure that the product is used in accordance with the manufacturer's instructions.
- Always inspect the scope rings for any damage or wear before use.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe conditions or incidents to the relevant authorities.
- Regularly check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- The MAX50 SCOPE RINGS are designed for use with scopes that have a 30mm tube diameter. Ensure compatibility before installation.
- Avoid overtightening the screws during installation to prevent damage to the scope and rings.
- Do not use the scope rings if they show signs of damage or if the screws are stripped.
- Always ensure that the scope is securely mounted before handling the firearm.
- Be aware of the potential hazards associated with the .50 BMG round and ensure that all safety protocols for handling firearms are followed.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary tools, including a Torx screwdriver compatible with #840 screws.
- Ensure that the workspace is clean and free of obstructions.

2. Installation Steps

- Place the scope rings onto the desired mounting surface on the firearm.
- Align the rings with the scope tube, ensuring they are positioned correctly.
- Insert the #840 Torx screws into the designated holes of the scope rings.
- Gently tighten each screw in a crisscross pattern to ensure even pressure. Avoid overtightening.

3. Usage

- Once installed, check the alignment and stability of the scope.
- Conduct a test to ensure that the scope holds zero after installation.
- Regularly check the tightness of the screws, especially after extensive use or exposure to harsh conditions.

Disposal Instructions

- Dispose of the MAX50 SCOPE RINGS in accordance with local regulations for aluminum and steel products.
- Do not dispose of the product in household waste. Instead, utilize designated recycling facilities.

Contact Information for Further Support

For any safety inquiries or further assistance, please contact the manufacturer or visit their website for more information.

Thank you for your attention to these safety guidelines. Your safety and satisfaction are our top priorities.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at