

TSR PICATINNY SCOPE RINGS - TPS PRODUCTS 1" LOW (0.785") ALUMINUM RINGS

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Super Holding Power, Precision Alignment

TSR Series Rings, precisely machined from an aluminum billet, with tolerances held to .0002", give maximum scope/ring contact. Holds scope securely against recoil. Four-screw cap lets you align the reticle, tighten the left side of the cap, then the right side without the scope rotating. Radiused edges and corners help prevent snagging while providing attractive appearance. Large, clamp-nut lets you torque rings to Mil-STD 1913 (Picatinny) bases.



Attributes

- Name: [TPS PRODUCTS 1" LOW \(0.785"\) ALUMINUM RINGS](#)
- Manufacturer: [TPS PRODUCTS](#)
- Product no.: 100000951
- Mfr. No.: 30520
- Finish: Matte Blue
- Height: .785"
- Material: Aluminum
- Scope Tube Diameter: 1"
- Size: Low
- Style: Tactical Rings
- Delivery weight: 0.159kg
- Shipping height: 61mm
- Shipping width: 61mm
- Shipping length: 94mm
- UPC: 071611305204

Item details

Made in USA

Table of Contents

- Startpage
- TSR Picatinny Scope Rings Safety Instruction Guide
- About Us

TSR Picatinny Scope Rings Safety Instruction Guide

Introduction

Thank you for choosing the TSR Picatinny Scope Rings by TPS Products. This guide provides important safety information and instructions to ensure the safe and effective use of your scope rings. Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Inspect the scope rings for any damage before installation. Do not use if damaged.
- Keep the product out of reach of children and vulnerable individuals.
- Follow all local laws and regulations regarding firearm accessories.
- Always wear appropriate safety gear when handling firearms.
- Report any unsafe products or accidents to the relevant authorities.
- Check for updates on product recalls via the EU's Safety Gate platform.

Specific Safety Precautions for Use

• Potential Hazards:

- Improper installation may lead to scope misalignment and potential accidents.
- Excessive torque can damage the scope rings or the firearm.

• Avoiding Hazards:

- Do not exceed the recommended torque specifications when securing the rings.
- Ensure that the scope is properly aligned before tightening.
- Regularly check the tightness of the rings after use.
- Use caution when handling firearms equipped with the scope rings.

Instructions for Installation and Usage

1. Installation:

- Gather necessary tools: a torque wrench and a flathead screwdriver.
- Ensure the firearm is unloaded and pointed in a safe direction.
- Place the scope rings on the Picatinny rail, ensuring they fit securely.
- Align the scope within the rings and adjust for proper eye relief.
- Tighten the left side screw of the ring cap to hold the scope in place.
- After securing the left side, tighten the right side screw carefully.
- Use the torque wrench to apply the recommended torque to the screws (consult the product specifications for exact values).

2. Usage:

- After installation, check the alignment of the scope reticle.
- During use, periodically check the scope rings for tightness and stability.
- If you notice any movement or misalignment, stop using the firearm and recheck the installation.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of aluminum rings in regular household waste; check for recycling options.
- Ensure that any packaging materials are disposed of responsibly.

Contact Information for Further Support

For any questions or concerns regarding the TSR Picatinny Scope Rings, please contact the manufacturer directly through the appropriate channels provided with your product documentation.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk