

TSR PICATINNY SCOPE RINGS - 1" HIGH (1.185") ALUMINUM RINGS

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Super Holding Power, Precision Alignment

TSR Series Rings, precisely machined from an aluminum billet, with tolerances held to .0002", give maximum scope/ring contact. Holds scope securely against recoil. Four-screw cap lets you align the reticle, tighten the left side of the cap, then the right side without the scope rotating. Radiused edges and corners help prevent snagging while providing attractive appearance. Large, clamp-nut lets you torque rings to Mil-STD 1913 (Picatinny) bases.



Attributes

- Name: [1" HIGH \(1.185"\) ALUMINUM RINGS](#)
- Manufacturer: [TPS PRODUCTS](#)
- Product no.: 100000953
- Mfr. No.: 30522
- Finish: Matte Blue
- Height: 1.185"
- Material: Aluminum
- Scope Tube Diameter: 1"
- Size: High
- Style: Tactical Rings
- Delivery weight: 0.181kg
- Shipping height: 58mm
- Shipping width: 61mm
- Shipping length: 94mm
- UPC: 071611305228

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [TSR Picatinny Scope Rings Safety Instruction Guide](#)
- [About Us](#)

TSR Picatinny Scope Rings Safety Instruction Guide

Introduction

Thank you for choosing the TSR Picatinny Scope Rings. These highquality aluminum rings are designed to provide secure and reliable mounting for your scope. This guide provides essential safety instructions to ensure the proper use and handling of the product, in compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Always read and understand this safety instruction guide before using the product.
- Ensure that the scope rings are compatible with your specific scope and firearm.
- Inspect the scope rings for any damage or defects before installation. Do not use damaged products.
- Ensure that the scope is properly mounted and secured to avoid accidents.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe conditions or accidents to the relevant authorities.

Specific Safety Precautions for Use

- When mounting your scope, ensure that the rings are tightened securely to prevent movement during use.
- Use the appropriate tools to avoid overtightening, which can damage the scope or rings.
- Align the reticle properly before securing the cap to avoid misalignment during shooting.
- Be aware of your surroundings and ensure that the firearm is pointed in a safe direction at all times.
- Always follow the manufacturer's instructions for the scope and firearm you are using.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools for installation, including a torque wrench and screwdriver.
- Ensure that your firearm is unloaded and pointed in a safe direction.

2. Installation:

- Place the scope rings on the Picatinny rail of your firearm.
- Align the rings to the desired position on the rail.
- Use the four screws on the cap to secure the scope rings:
 - Tighten the left side of the cap first to align the reticle.
 - Follow by tightening the right side to secure the scope without rotation.
- Ensure that the rings are torqued to MilSTD 1913 specifications.

3. Usage:

- Once installed, check the alignment of the scope and make any necessary adjustments.
- Regularly inspect the rings and scope for any signs of wear or loosening.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.

- Consider recycling the aluminum material where facilities are available.

Contact Information for Further Support

For any safety inquiries or support, please contact the manufacturer directly. Ensure you have the product details available for reference.

Thank you for your attention to these safety instructions. Safe handling and proper use of your TSR Picatinny Scope Rings will enhance your shooting experience.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at