

RIFLE CREEDMOOR UNIVERSAL LONG RANGE 3" - DAVIDE PEDERSOLI S.R.L RIFLE ADJ TANG CREEDMOOR UNIVERSAL LONG RANGE 3" BLACK

[Rifle Parts](#) > [Sights](#) > [Rear Sights](#)

Named after the famous range on Long Island that hosted many long-range rifle competitions in the 1870s and '80s, the Creedmoor ladder-type sight is fully adjustable for windage and elevation and works equally well on cartridge rifles and muzzleloaders. Sight is precision machined from steel and attaches to tang with supplied setscrews and folds down when not in use. The Universal model is available in middle-range 2" and long-range 3" heights. The windage adjustment mechanism is on the eyepiece, allowing the eyepiece to drop close to the base for close-in shots. The Soule model provides maximum adjustability to fit any hunting or target shooting conditions. Elevation is adjustable in precise increments of 1 MOA, and one full turn of the windage knob moves the point of aim left or right by 2½ MOA in ½ minute increments. Large knurled knob at the sight base allows fast, accurate return to center or previous setting. Choice of Short, Middle, and Long Range models. The "Goodwin" style sight was a popular sight for long range shooters in the late 1800s. The "flag" position allows for a very wide windage adjustment range of 1.26". The elevation adjustment on the Goodwin has a range of 3.94". With the Goodwin's structure, the chamber can be easily accessed for cleaning or inspection. The Goodwin also has a "tilt" screw that allows the staff to be perfectly vertical at all elevations.



Attributes

- Name: [DAVIDE PEDERSOLI S.R.L RIFLE ADJ TANG CREEDMOOR UNIVERSAL LONG RANGE 3" BLACK](#)
- Manufacturer: [DAVIDE PEDERSOLI S.R.L](#)
- Product no.: 100002376
- Mfr. No.: USA 430
- Colour: Black
- Style: Adjustable,Tang Sights
- Weapon type: Universal Rifles
- Delivery weight: 0.249kg
- Shipping height: 43mm
- Shipping width: 117mm
- Shipping length: 213mm

Table of Contents

- Startpage
- Safety Instruction Guide for RIFLE CREEDMOOR UNIVERSAL LONG RANGE 3"
- About Us

Safety Instruction Guide for RIFLE CREEDMOOR UNIVERSAL LONG RANGE 3"

Introduction

Thank you for choosing the RIFLE CREEDMOOR UNIVERSAL LONG RANGE 3" by Davide Pedersoli S.R.L. This product is designed for precision shooting and offers adjustable features for enhanced performance. To ensure safe and effective use, please read this safety instruction guide thoroughly before installation and use.

General Safety Guidelines

- Always treat your rifle as if it is loaded.
- Keep the rifle pointed in a safe direction at all times.
- Ensure that the area is clear of people and obstacles before shooting.
- Always wear appropriate eye and ear protection when using this product.
- Store the rifle in a secure place, out of reach of children and unauthorized users.
- Regularly check the equipment for wear and tear to prevent malfunctions.
- Be aware of your surroundings and follow local laws and regulations regarding firearm use.

Specific Safety Precautions for Use

- Ensure that the sight is correctly installed and securely fastened before use.
- Avoid making adjustments to the sight while aiming at a target.
- Do not exceed the manufacturer's recommended adjustments for windage and elevation.
- Be cautious when using the Goodwin style sight, particularly the "tilt" screw, to maintain proper vertical alignment.
- If you notice any irregularities in the sight's performance, cease use immediately and seek professional assistance.
- Keep the sight clean and free of obstructions to ensure optimal functionality.

Instructions for Installation and Usage

1. Preparation

- Ensure the rifle is unloaded and in a safe condition before starting the installation.
- Gather necessary tools, including a screwdriver and provided mounting screws.

2. Installation Steps

- Locate the tang of the rifle where the sight will be mounted.
- Align the sight with the mounting holes on the tang.
- Use the provided setscrews to attach the sight securely to the tang. Ensure that the sight is firmly in place.
- If required, drill and tap the tang according to the specifications provided (Distance between mounting holes: 2.20" 2.29" or 5.6 5.8 cm).
- After installation, check that the sight is stable and does not wobble.

3. Usage Steps

- Adjust the eyepiece for windage by turning the adjustment knob. Make sure to do this while the rifle is pointed in a safe direction.
- Elevate the sight by turning the elevation knob in precise increments of 1 MOA.
- Familiarize yourself with the adjustments to understand how they affect your point of aim.

- Perform test shots to ensure that the sight is properly calibrated for your shooting conditions.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the sight in regular household waste.
- Consider recycling options for metal components where available.

Contact Information for Further Support

For any inquiries or concerns regarding the RIFLE CREEDMOOR UNIVERSAL LONG RANGE 3", please refer to the manufacturer's contact information provided with your product packaging. It is important to have a point of contact for safety inquiries and support.

By following these safety instructions, you can enjoy the full benefits of your RIFLE CREEDMOOR UNIVERSAL LONG RANGE 3" while ensuring a safe shooting experience. Always prioritize safety and responsibility in all your shooting activities.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk