

AR-15 USGI BACKUP IRON REAR SIGHT - MATECH AR-15 FLIP-UP ADJ USGI BACKUP IRON REAR SIGHT BLACK

[Rifle Parts](#) > [Sights](#) > [Rear Sights](#)

U.S. Army Standard-Issue Backup Sight For M4/M16A4

Current U.S. Army standard-issue backup rear sight for M4 carbines and M16A4 rifles flips up instantly at the touch of your thumb when primary sight fails or tactical situation makes iron sights preferable. Designed in conjunction with Picatinny Arsenal engineering staff and rigorously tested at Fort Benning and Aberdeen Proving Ground for robustness, ease of use, and effective targeting out to 600 meters. Detent-locking lever lets you quickly switch to one of eight range settings: 200, 300, 350, 400, 450, 500, 550, and 600 meters. Adjust windage easily with grooved, A2-style windage knob and position markers on the back of the sight for repeatability of settings. Bright, white, laser etched numbers and markers are clearly visible even in low light. Rugged machined steel construction ensures sight retains zero even under heavy, full-auto fire. Clamps securely to the rearmost slot of MIL-STD 1913 Picatinny or Weaver-style accessory rail on flattop receiver via simple but strong locking bar and bolt. Rounded corners and beveled edges further reduce danger of snagging on other gear when sight post is down. Regulates correctly with A2 front sight on any AR-15-style rifle or carbine; instructions included for adjusting front sight post height to set exact zero. Designed to co-witness with most non-magnifying optical sights.



Attributes

- Name: [MATECH AR-15 FLIP-UP ADJ USGI BACKUP IRON REAR SIGHT BLACK](#)
- Manufacturer: [MATECH](#)
- Product no.: 100003702
- Mfr. No.: 12996812-C
- Colour: Black
- Style: Adjustable,Flip-Up Sights
- Weapon type: AR-15
- Delivery weight: 0.113kg
- Shipping height: 5mm
- Shipping width: 89mm
- Shipping length: 157mm

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for AR15 USGI Backup Iron Rear Sight
- About Us

Safety Instruction Guide for AR15 USGI Backup Iron Rear Sight

Introduction

Thank you for choosing the AR15 USGI Backup Iron Rear Sight by MATECH. This product is designed to enhance your shooting experience with reliable performance and ease of use. To ensure safe and effective operation, please read and follow this safety instruction guide carefully.

General Safety Guidelines

- Always treat firearms and accessories as if they are loaded and ready to fire.
- Keep the firearm pointed in a safe direction at all times.
- Ensure that the area is clear of unauthorized persons when handling firearms.
- Use appropriate safety gear, including eye and ear protection, when using firearms.
- Familiarize yourself with your firearm and its components, including the rear sight.
- Only use the rear sight with compatible AR15 style rifles or carbines.
- Store the rear sight and firearm in a secure location, away from children and unauthorized users.
- Regularly inspect the rear sight for wear, damage, or loose components before use.

Specific Safety Precautions for Use

• Potential Hazards:

- Improper installation may lead to malfunction or failure.
- Adjusting the sight while the firearm is loaded poses a risk of accidental discharge.
- Using the sight with incompatible firearms may result in inaccurate targeting or injury.

• Instructions for Avoiding Hazards:

- Always ensure the firearm is unloaded before installing or adjusting the rear sight.
- Follow the installation instructions precisely to avoid improper setup.
- Do not attempt to modify or alter the rear sight in any way.
- Keep hands and fingers clear of the sighting mechanism when adjusting settings.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Locate the rearmost slot of the MILSTD 1913 Picatinny or Weaverstyle accessory rail on your flattop receiver.
- Align the rear sight with the rail and slide it into position.
- Secure the sight using the locking bar and bolt provided. Ensure it is tightened adequately to prevent movement.

2. Adjusting the Sight:

- Use the detentlocking lever to select one of the eight range settings: 200, 300, 350, 400, 450, 500, 550, or 600 meters.
- To adjust windage, turn the A2style windage knob. The position markers on the back of the sight will help you maintain repeatability.

- Ensure that the adjustments are made with the firearm unloaded and pointed in a safe direction.

3. CoWitnessing:

- The rear sight is designed to cowitness with most nonmagnifying optical sights. Ensure proper alignment for accurate targeting.

Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic and metal waste.
- Do not dispose of the sight in regular household waste.
- Contact your local waste management authority for specific disposal instructions.

Contact Information for Further Support

For questions or concerns regarding the AR15 USGI Backup Iron Rear Sight, please refer to the manufacturer's website or contact their customer service directly. Ensure you have the product information ready for assistance.

By following these safety instructions, you can ensure a safe and enjoyable experience with your AR15 USGI Backup Iron Rear Sight. Always prioritize safety and responsible handling of firearms and accessories.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk