

# AR-15 FLIP-UP HK-STYLE DUAL APERTURE FRONT SIGHT - 1.3" FLIP-UP HK-STYLE DUAL APERTURE FRONT SIGHT SS BLACK

[Rifle Parts](#) > [Sights](#) > [Front Sights](#)

Rugged, flip-up sights provide failsafe backup when your primary optic or red dot sight fails. Sight body flips up easily when you need it and locks securely in place under powerful spring pressure and two locking detent balls, so it can't be accidentally bumped down until you hit the spring-loaded button on the left side of the base to retract it. Positions apertures at the same height as factory sights, simplifying integration of these sights on your rifle. Base clamps securely to any military or commercial Picatinny rail using a standard flathead screwdriver. No protruding knobs or levers to catch on brush, clothing, or other equipment. Sturdy, protective "ears" shield posts and apertures from impact. Front sights clamp to handguard accessory rail on the same plane as flattop and are only 1/2" high when folded. All models have M4-type post that's elevation adjustable in 1/2 MOA increments. HK-Style Front - distinctive "globe" shape that aids in fast target acquisition under stress. Also available with a self-illuminating Tritium dot on the post for precise shot placement in low-light conditions.



## Attributes

- Name: [1.3" FLIP-UP HK-STYLE DUAL APERTURE FRONT SIGHT SS BLACK](#)
- Manufacturer: [TROY INDUSTRIES](#)
- Product no.: 100005084
- Mfr. No.: SSIG-FBS-FHBT-02
- Color: Black
- Height: 1.3
- Make: AR-15
- Material: Stainless Steel
- Style: Flip-Up
- Delivery weight: 0.068kg
- Shipping height: 10mm
- Shipping width: 142mm
- Shipping length: 201mm
- UPC: 812699011072

## Item details

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for AR15 FlipUp HKStyle Dual Aperture Front Sight
- About Us

# Safety Instruction Guide for AR15 FlipUp HKStyle Dual Aperture Front Sight

## Introduction

Thank you for choosing the AR15 FlipUp HKStyle Dual Aperture Front Sight. This product is designed to provide reliable backup aiming solutions for your rifle. To ensure safe use and optimal performance, please carefully read and follow the safety instructions outlined in this guide.

## General Safety Guidelines

- Always treat your firearm and its accessories with respect and care.
- Ensure that you are familiar with the operation of your firearm before using this sight.
- Regularly inspect the sight for any signs of wear or damage.
- Ensure that the sight is securely mounted before each use.
- Keep the sight and your firearm clean and free from debris.
- Store your firearm and accessories in a safe place, away from children and unauthorized users.
- Report any unsafe products or incidents to the appropriate authorities.
- Check for recall updates on the EU's Safety Gate platform.

## Specific Safety Precautions for Use

- Ensure that the sight is only used with compatible firearms, specifically the AR15 model.
- Do not attempt to modify or alter the sight in any way.
- Avoid using the sight in extreme weather conditions that may affect its performance.
- Use caution when flipping the sight up or down; ensure your hands are clear of moving parts.
- Be aware of your surroundings and ensure a clear line of sight when aiming.
- Do not use the sight if you notice any damage or malfunction.
- If using the selfilluminating Tritium dot version, be aware of the proper handling and storage requirements for Tritium.

## Instructions for Installation and Usage

### Installation Instructions

1. **Gather Tools:** You will need a standard flathead screwdriver for installation.
2. **Position the Sight:** Align the base of the sight with the desired location on your rifle's Picatinny rail.
3. **Secure the Sight:**
  - Insert the screws into the mounting holes.
  - Tighten the screws using the flathead screwdriver until the sight is firmly attached.
4. **Check Stability:** Ensure that the sight does not move or wobble once installed.

### Usage Instructions

1. **Flipping Up the Sight:**
  - To use the sight, press the springloaded button located on the left side of the base.
  - Gently flip the sight up until it locks into place.
2. **Adjusting the Aperture:**
  - Use the M4type post to adjust elevation in  $\frac{1}{2}$  MOA increments as needed.
3. **Flipping Down the Sight:**
  - To retract the sight, press the springloaded button again and gently push the sight down until it locks.
4. **Maintaining the Sight:**
  - Regularly clean the sight with a soft cloth to remove dirt and debris.

- Inspect the sight for any signs of wear or damage before each use.

## **Disposal Instructions**

- Dispose of the sight in accordance with local regulations.
- Do not dispose of the sight in regular household waste.
- If the sight contains any hazardous materials, ensure proper handling and disposal according to safety guidelines.

## **Contact Information for Further Support**

For any inquiries or concerns regarding the safety and performance of your AR15 FlipUp HKStyle Dual Aperture Front Sight, please refer to the product packaging or your retailer for contact information.

Thank you for your attention to these safety instructions. Enjoy using your AR15 FlipUp HKStyle Dual Aperture Front Sight safely and responsibly.

# About Us

## Brownells Austria

**Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

[www.brownells.at](http://www.brownells.at)