

LOW-PROFILE SLING MOUNT

[Shooting Accessories](#) > [Slings & Sling Swivels](#) > [Tactical Sling Mounts](#)

Instant Sling Attachment Point On Any Picatinny Rail

Low-profile, aluminum mount clamps to any Picatinny rail to provide an attachment point for a quick-detach, pushbutton sling swivel exactly where you need it. Recessed crossbolt and locking bar attachment system installs with a flat-blade screwdriver—no protruding hex nuts to snag other gear. Limits swivel rotation to 45° to help prevent sling tangling.



Attributes

- Name: [LOW-PROFILE SLING MOUNT](#)
- Manufacturer: [VIKING TACTICS](#)
- Product no.: 100005521
- Mfr. No.: VTAC-LPSM
- Color: Matte Black
- Delivery weight: 0.045kg
- Shipping height: 1mm
- Shipping width: 83mm
- Shipping length: 146mm

Item details

Made in USA

Table of Contents

- Startpage
- **LOWPROFILE SLING MOUNT Safety Instructions**
- About Us

LOWPROFILE SLING MOUNT Safety Instructions

Introduction

Thank you for choosing the LOWPROFILE SLING MOUNT by VIKING TACTICS. This product is designed to enhance your tactical gear setup by providing a secure attachment point for a quickdetach, pushbutton sling swivel. Please read this safety instruction guide carefully to ensure safe usage and installation.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose as a tactical sling mount.
- Regularly inspect the sling mount for any signs of damage or wear before each use.
- Keep the product out of reach of children and vulnerable individuals.
- Do not modify the sling mount in any way, as this may compromise safety.
- Always follow the installation instructions to prevent accidents or injuries.
- Report any unsafe conditions or incidents related to the product to the appropriate authorities.

Specific Safety Precautions for Use

- Verify that the Picatinny rail on your equipment is compatible with the LOWPROFILE SLING MOUNT.
- Ensure that the locking bar is securely fastened before using the sling mount.
- Limit swivel rotation to 45° to prevent sling tangling and ensure proper functioning.
- Avoid overloading the sling mount beyond its specified weight capacity.
- Do not use the sling mount if any components are damaged or missing.

Instructions for Installation and Usage

1. Installation

- Use a flatblade screwdriver for installation.
- Align the LOWPROFILE SLING MOUNT with the desired position on the Picatinny rail.
- Securely tighten the recessed crossbolt and locking bar attachment system.
- Confirm that the mount is stable and does not wobble.

2. Usage

- Attach your quickdetach, pushbutton sling swivel to the sling mount.
- Ensure that the sling swivel is properly engaged before use.
- Regularly check the attachment point during use to ensure it remains secure.

Disposal Instructions

- Dispose of the LOWPROFILE SLING MOUNT in accordance with local regulations.
- Recycle materials whenever possible to minimize environmental impact.

Contact Information for Further Support

For any questions or concerns regarding the LOWPROFILE SLING MOUNT, please refer to the manufacturer's website or customer service for assistance. Ensure that you have the product details and any relevant information available when seeking support.

Thank you for your attention to these safety instructions. Your safety is our priority.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at