

# FRONT SIGHT SCREWS for GLOCK® - WARREN TACTICAL SERIES

## FRONT SIGHT SCREWS FOR GLOCK®, 5-PACK

[Handgun Parts](#) > [Sights](#) > [Sight Parts](#) > [Sight Screws](#)

### Non-Corroding Stainless Steel Replacements For Aftermarket Sights

Stainless steel screws have the standard Glock® 3/16" hexagonal head but a shorter shank for correct fit on threaded aftermarket front sights from Warren Tactical, Novak, Trijicon, and others. Inexpensive, corrosion-resistant replacements for lost or dinged up screws that came with your sights. Fits standard Glock® front sight tool. Use with thread-locking agent to ensure a secure installation. Recommended for all Warren front sights for Glock®, including Tactical, Sevigny, Fiber Optic, and Tritium Night Sight models sold individually and in sets. Available in 2- and 5-Paks.



### Attributes

- Name: [WARREN TACTICAL SERIES FRONT SIGHT SCREWS FOR GLOCK®, 5-PACK](#)
- Manufacturer: [WARREN TACTICAL SERIES](#)
- Product no.: 100006817
- Mfr. No.: FSSCREW316HEX5P
- Model: Universal Handguns
- Weapon type: Glock
- Delivery weight: 0.045kg
- Shipping width: 83mm
- Shipping length: 146mm

### Item details

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for FRONT SIGHT SCREWS for GLOCK® WARREN TACTICAL SERIES
- About Us

# Safety Instruction Guide for FRONT SIGHT SCREWS for GLOCK® WARREN TACTICAL SERIES

## Introduction

Thank you for choosing the FRONT SIGHT SCREWS for GLOCK® WARREN TACTICAL SERIES. This guide provides essential safety information and instructions for the proper use and installation of these screws. Please read this guide carefully to ensure safe and effective use.

## General Safety Guidelines

- Always ensure that the firearm is unloaded before installing or replacing any parts.
- Use only the recommended tools for installation to avoid damaging the screws or the firearm.
- Keep screws and tools out of reach of children and vulnerable individuals.
- Inspect the screws and the front sight for any signs of damage before installation.
- If you notice any defects or issues, do not use the screws and contact a qualified professional for assistance.
- Follow all local laws and regulations regarding firearm modifications and accessories.

## Specific Safety Precautions for Use

- Ensure that the FRONT SIGHT SCREWS are compatible with your specific model of GLOCK® and the front sight you are using.
- Use a threadlocking agent during installation to prevent screws from loosening due to recoil.
- Do not overtighten the screws, as this may strip the threads or damage the front sight.
- If you experience any difficulty during installation, seek assistance from a qualified gunsmith.
- Avoid using the screws in extreme weather conditions, as this may affect their performance.

## Instructions for Installation and Usage

### 1. Preparation

- Ensure the firearm is unloaded.
- Gather necessary tools: a standard GLOCK® front sight tool and a threadlocking agent.

### 2. Removing Old Screws

- Use the front sight tool to remove the existing screws from the front sight.
- Carefully set aside any removed screws for proper disposal.

### 3. Installing New Screws

- Take the FRONT SIGHT SCREWS and apply a small amount of threadlocking agent to the threads.
- Align the front sight with the slide and insert the new screws into the threaded holes.
- Use the front sight tool to tighten the screws gently. Ensure they are snug but do not overtighten.

### 4. Final Inspection

- Check that the front sight is securely attached and that the screws are properly tightened.
- Conduct a function check of the firearm to ensure everything is operating correctly.

## **Disposal Instructions**

- Dispose of any old screws and packaging materials in accordance with local waste management regulations.
- Do not dispose of screws in a manner that could pose a risk to the environment or public safety.

## **Contact Information for Further Support**

For any questions or concerns regarding the FRONT SIGHT SCREWS for GLOCK® WARREN TACTICAL SERIES, please consult a qualified firearms professional or contact the manufacturer directly.

By following these safety instructions, you can ensure a secure and effective installation of your FRONT SIGHT SCREWS. Thank you for prioritizing safety in your firearm maintenance.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)