

RUGER 10/22™ ADJUSTABLE FRONT SIGHT .920" BARREL - NODAK SPUD LLC .505" ADJ FRONT SIGHT FOR RUGER 10/22 .920" BBL ALUM BLK

[Rifle Parts](#) > [Sights](#) > [Front Sights](#)

Nodak spud front sight Allow 10/22® to have similar sight picture to military type rifles such as the AR-15/M16 Works with standard 10/22® barrels Uses SKS post secured w/ two 10-32 nylon tipped set screws Has wide range of elevation adjustment Works with a variety of receiver mounted 10/22® sights Requires a SKS/AK style sight adjustment tool for elevation adjustment Use with Ruger® 10/22® Rear Sight w/Rail



Attributes

- Name: [NODAK SPUD LLC .505" ADJ FRONT SIGHT FOR RUGER 10/22 .920" BBL ALUM BLK](#)
- Manufacturer: [NODAK SPUD LLC](#)
- Product no.: 100007239
- Mfr. No.: NDS-23
- Color: Black
- Height: .505
- Make: Ruger
- Material: Aluminum
- Model: 10/22
- Style: Adjustable
- Delivery weight: 0.023kg

Item details

Made in USA

Table of Contents

- Startpage
- RUGER 10/22™ Adjustable Front Sight Safety Instruction Guide
- About Us

RUGER 10/22™ Adjustable Front Sight Safety Instruction Guide

Introduction

Thank you for choosing the RUGER 10/22™ Adjustable Front Sight. This guide provides important safety instructions and usage guidelines to ensure your product operates safely and effectively. Please read this document carefully before installation and use.

General Safety Guidelines

- Always handle the sight with care to prevent damage.
- Ensure that you are familiar with the operation of your Ruger 10/22® firearm before installation.
- Keep the product out of reach of children and unauthorized users.
- Use the sight only for its intended purpose and in accordance with the manufacturer's instructions.
- Regularly inspect the sight for any signs of wear or damage before use.
- If you notice any defects or malfunctions, discontinue use immediately and seek professional assistance.

Specific Safety Precautions for Use

- Always ensure that the firearm is unloaded before installing or adjusting the front sight.
- Use the appropriate SKS/AK style sight adjustment tool for elevation adjustments.
- Avoid using excessive force when securing the sight to prevent damage to the firearm or the sight itself.
- Be aware of your surroundings and ensure that you are in a safe environment when using the firearm.
- Follow all local laws and regulations regarding the use of firearms and accessories.

Instructions for Installation and Usage

1. Preparation

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather necessary tools, including the SKS/AK style sight adjustment tool and any required screws.

2. Installation

- Remove the existing front sight from the Ruger 10/22® barrel.
- Align the Nodak Spud front sight with the barrel, ensuring it fits securely.
- Use the two 1032 nylon tipped set screws to secure the sight in place. Tighten gently to avoid damage.
- Adjust the elevation using the SKS/AK style sight adjustment tool as needed.

3. Usage

- Once installed, check the alignment of the sight with the rear sight for proper sight picture.
- Make any necessary adjustments to achieve the desired sight picture.
- Always verify the sight's functionality before heading to the range or field.

Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic and metal waste.
- Do not dispose of the product in regular household waste.
- If the product is damaged or no longer usable, consider recycling components where possible.

Contact Information for Further Support

For any questions or concerns regarding the RUGER 10/22™ Adjustable Front Sight, please contact the manufacturer directly or refer to the product website for further assistance.

By following these guidelines, you can ensure safe and effective use of your RUGER 10/22™ Adjustable Front Sight. Thank you for your attention to safety, and enjoy your shooting experience!

About Us

Brownells Europe

Brownells Europe - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

P.O.Box 4300
Warwick
CV34 9BR

www.brownells.eu