

BREECH LOCK QUICK CHANGE BUSHING - LEE PRECISION LEE QUICK LOCK BUSHINGS

[Reloading](#) > [Reloading Dies](#) > [Replacement Parts & Upgrades](#)

Pack of (2) Breech Lock Quick Change Bushings Allows instant, accurate die changes Fits Lee reloading presses with the Breech Lock System



Attributes

- Name: [LEE PRECISION LEE QUICK LOCK BUSHINGS](#)
- Manufacturer: [LEE PRECISION](#)
- Product no.: 100010150
- Mfr. No.: 90600
- Delivery weight: 0.091kg
- Shipping height: 25mm
- Shipping width: 89mm
- Shipping length: 127mm
- UPC: 734307906009

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for BREECH LOCK QUICK CHANGE BUSHING
- About Us

Safety Instruction Guide for BREECH LOCK QUICK CHANGE BUSHING

Introduction

Thank you for choosing the BREECH LOCK QUICK CHANGE BUSHING from Lee Precision. This product is designed to enhance your reloading experience by allowing for quick and accurate die changes. To ensure safe use and compliance with the EU General Product Safety Regulation (GPSR), please read this safety instruction guide carefully before using the product.

General Safety Guidelines

- Always use the product according to the manufacturer's instructions.
- Keep the product out of reach of children and vulnerable individuals.
- Inspect the product for any damage or wear before use. Do not use if damaged.
- Report any unsafe conditions or accidents to the relevant authorities.
- Stay informed about any product recalls by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Ensure that the Breech Lock Quick Change Bushings are compatible with your Lee reloading press.
- Do not force the bushings into the press; they should fit securely without excessive pressure.
- Avoid using the product in wet or damp conditions to prevent electrical hazards.
- Wear appropriate safety gear, such as safety glasses, when using the reloading press.
- Do not modify or alter the product in any way, as this may compromise safety.

Instructions for Installation and Usage

1. Installation:

- Ensure the reloading press is turned off and unplugged.
- Remove any existing bushings from the press.
- Align the Breech Lock Quick Change Bushing with the mounting point on the press.
- Gently push the bushing into place until it clicks securely.
- Repeat the process for any additional bushings as needed.

2. Usage:

- After installation, ensure that the bushing is securely locked in place.
- To change dies, simply pull the locking ring on the bushing and remove the die.
- Insert the new die into the bushing and push down until it locks into place.
- Always doublecheck that the die is securely fastened before operating the press.

Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic waste and materials.
- Do not throw the product in regular household waste.
- If the product is damaged or no longer usable, contact local waste management services for proper disposal methods.

Contact Information for Further Support

For any inquiries regarding safety or usage of the BREECH LOCK QUICK CHANGE BUSHING, please consult the manufacturer's website or customer support resources. Always ensure you have the latest information and guidance.

By following these safety guidelines and instructions, you can ensure a safe and effective reloading experience with your BREECH LOCK QUICK CHANGE BUSHING. Thank you for your attention to safety!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk