

MS3® GEN2 SINGLE QD MULTI-MISSION ONE/TWO-POINT RIFLE SLING - MAGPUL MS3 GEN2 SINGLE QD ONE/TWO-POINT RIFLE SLING BLACK

[Shooting Accessories](#) > [Slings & Sling Swivels](#) > [Slings](#)

Filling the same mission requirement as the standard MS3 Sling, the MS3 Single QD can quickly switch between one-point and two-point configuration. The MS3 Single QD maintains material construction and specifications identical to that of the standard MS3, but features a heavy-duty push-button QD Sling Swivel for the one-point (rear) weapon attachment rather than the Magpul Paraclip™. This modification allows compatibility with QD sling cups commonly found on lower receivers, receiver end plates, and buttstocks. The MS3 Single QD GEN2 incorporates a new low profile quick-adjust Slider which minimizes bulk and allows for secure, yet effortless, sling adjustment.

Webbing length has also been increased for a comfortable fit with all body types and armor configurations. Made in USA and 100% Berry Amendment compliant. NSN: MAG515-COY 1005-01-657-7616 FEATURES THE MS1® SLIDER Rapidly adjustable for length (shorter or longer) with new MS1 Slider Low-profile adjustment Slider for adding or removing sling tension in two-point mode with a single-hand MULTIPLE CONFIGURATIONS Designed for easy rapid convertability between one-point and two-point mode Heavy-duty push-button Quick Disconnect sling swivel for one-point attachment Paraclip shackle allows for fast transition between one-point and two-point configuration Cross-Bolt Lock Bar in the Paraclip allows the user to optionally lock its lever closed for extra security MAGPUL POLYMER AND INDESTRUCTIBLE HARDWARE

Lightweight heavy-duty reinforced polymer hardware Steel Paraclip lever is case hardened and finished with a QPQ salt bath nitride process for extreme resistance to wear and corrosion SNAG-FREE, HIGH DURABILITY WEBBING Custom 1.25 inch wide nylon webbing material is strong and wear resistant while remaining anti-chaff for user comfort No tails, loops, or other potential snag hazards Colored webbing has Near Infrared (NIR) treatment to reduce IR signature SPECS Length, Overall Nominal: 48-60 in. ± 5 in. adjustment Slider Adjustment Range: 10 in. Width, Webbing: 1.25" SLING MOUNTING REAR - Works with the Magpul ASAP® for optimal shoulder transitioning in one-point mode as well as with other end plates, receivers, and buttstocks that have a QD sling socket FRONT - Compatible with the Magpul RSA®, M-LOK® Paraclip™ Sling Mount, MSA®, and shotgun Forward Sling Mounts, as well as many snap-hook style sling loops* and standard or QD sling swivels for use in two-point mode * Snap-hook style sling loops with an inner diameter of at least 3/8" are required, but 9/16" and larger will provide full range of motion of the Paraclip



Attributes

- Name: [MAGPUL MS3 GEN2 SINGLE QD ONE/TWO-POINT RIFLE SLING BLACK](#)
- Manufacturer: [MAGPUL](#)
- Product no.: 100013976
- Mfr. No.: MAG515-BLK
- Colour: Black
- Material: Nylon
- Style: Quick Detach

- Width: 1-1/4"
- Delivery weight: 0.272kg
- Shipping height: 51mm
- Shipping width: 114mm
- Shipping length: 445mm
- UPC: 873750010700

Item details

Made in USA

Table of Contents

- Startpage
- MS3® GEN2 Single QD MultiMission One/TwoPoint Rifle Sling Safety Instructions
- About Us

MS3® GEN2 Single QD MultiMission One/TwoPoint Rifle Sling Safety Instructions

Introduction

Thank you for choosing the MS3® GEN2 Single QD MultiMission One/TwoPoint Rifle Sling manufactured by Magpul. This safety instruction guide is designed to help you use the product safely and effectively, ensuring compliance with the EU General Product Safety Regulation (GPSR). Please read this guide carefully to understand how to use and maintain your sling safely.

General Safety Guidelines

- **Product Safety:** Ensure safe use of the MS3 Sling by following all instructions and safety precautions outlined in this guide.
- **Enhanced Recalls:** Stay informed about product recalls and safety notices. If you receive a recall notice, follow the instructions provided.
- **Online Shopping:** When purchasing online, ensure that the seller meets safety requirements and provides adequate product information.
- **Special Consumer Focus:** This product is not intended for use by children. Keep it out of reach of children and vulnerable individuals.
- **EU Contact Point:** For any safety inquiries, refer to the manufacturer's contact information provided with the product.
- **Rapid Alerts:** Regularly check the EU's Safety Gate platform for updates on product safety and recalls.

Specific Safety Precautions for Use

- **Proper Use:** Always use the sling as intended. It is designed for firearms and should not be used for any other purpose.
- **Inspection:** Before each use, inspect the sling for any signs of wear, damage, or malfunction. Do not use the sling if it is damaged.
- **Weight Limit:** Ensure that the sling is not overloaded beyond its designed weight capacity. Refer to the specifications for guidance.
- **Secure Attachment:** Make sure the sling is securely attached to the weapon and that all connections are properly engaged before use.
- **Avoid Snag Hazards:** Be aware of your surroundings and avoid any potential snag hazards that could catch the sling during use.
- **Training:** Familiarize yourself with the operation of the sling and practice using it in a safe environment before engaging in any activities with a firearm.

Instructions for Installation and Usage

1. Installation:

- Ensure the rifle is unloaded and pointed in a safe direction before attaching the sling.
- Identify the attachment points on your rifle (e.g., QD sling socket, receiver end plate).
- Attach the heavyduty pushbutton Quick Disconnect (QD) sling swivel to the designated QD socket on the rifle.
- For twopoint configuration, attach the other end of the sling to the second designated point on the rifle.
- Ensure that all connections are secure and properly locked in place.

2. Usage:

- To switch between onepoint and twopoint configurations, follow the instructions provided in the product manual.
- Adjust the sling length using the MS1 Slider for a comfortable fit. Ensure that the adjustment is secure before use.
- Practice transitioning from onepoint to twopoint mode in a safe environment to become familiar with the sling's functionality.

Disposal Instructions

- **Disposal:** When the sling has reached the end of its useful life or is damaged beyond repair, dispose of it responsibly.
- **Recycling:** Check local regulations for guidance on recycling materials. Some components may be recyclable, while others should be disposed of as general waste.
- **Environmental Considerations:** Do not dispose of the sling in a manner that could harm the environment. Follow local waste disposal guidelines.

Contact Information for Further Support

For any questions or concerns regarding the MS3® GEN2 Single QD MultiMission One/TwoPoint Rifle Sling, please refer to the manufacturer's contact information provided with the product packaging.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk