

AR-15/M16 URX BARREL NUT WRENCH - KNIGHTS ARMAMENT

AR15 URX BARREL NUT WRENCH 5.56

[Gunsmith Tools](#) > [Rifle Tools](#) > [Wrenches](#)

Designed Specifically For Use With URX Barrel Nuts

Steel barrel nut wrench is specifically designed for installing or removing URX II, URX III, and URX 3.1 barrel nuts. Fits torque wrench with $\frac{1}{2}$ " drive (not included). Recommended installation torque spec is 45-55 ft.-lbs.



Attributes

- Name: [KNIGHTS ARMAMENT AR15 URX BARREL NUT WRENCH 5.56](#)
- Manufacturer: [KNIGHTS ARMAMENT](#)
- Product no.: 100015204
- Mfr. No.: 20495
- Weapon type: AR-15
- Delivery weight: 0.023kg
- Shipping height: 61mm
- Shipping width: 61mm
- Shipping length: 94mm
- UPC: 819064010159

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for AR15/M16 URX Barrel Nut Wrench
- About Us

Safety Instruction Guide for AR15/M16 URX Barrel Nut Wrench

Introduction

Thank you for choosing the AR15/M16 URX Barrel Nut Wrench by Knights Armament. This tool is designed for the safe and effective installation and removal of URX II, URX III, and URX 3.1 barrel nuts. To ensure your safety and the proper functioning of this product, please read and follow the safety instructions outlined in this guide.

General Safety Guidelines

- Always use the wrench according to the manufacturer's instructions to avoid injury.
- Inspect the wrench before each use for any signs of damage or wear.
- Keep the wrench out of reach of children and vulnerable individuals.
- Do not use the wrench for any purpose other than its intended use.
- If you experience any difficulties or uncertainties while using the wrench, seek assistance from a qualified professional.

Specific Safety Precautions for Use

- Ensure that the torque wrench used with this product is rated for $\frac{1}{2}$ " drive and is in good working condition.
- Always wear appropriate personal protective equipment (PPE), such as safety glasses and gloves, while using the wrench.
- Be aware of your surroundings and ensure that there are no obstructions or hazards near your work area.
- Do not exceed the recommended installation torque specification of 4555 ftlbs.
- Avoid using excessive force; if the barrel nut does not turn, stop and assess the situation.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools and materials, including the AR15/M16 URX Barrel Nut Wrench and a compatible torque wrench.
- Ensure that the work area is clean, welllit, and free from distractions.

2. Installation:

- Place the barrel nut on the appropriate part of the firearm.
- Fit the barrel nut wrench onto the barrel nut, ensuring a secure grip.
- Attach the torque wrench to the barrel nut wrench.
- Gradually apply torque until the recommended specification of 4555 ftlbs is reached.
- Monitor the barrel nut for any signs of improper seating or damage during the process.

3. Removal:

- To remove the barrel nut, fit the barrel nut wrench onto the barrel nut as before.
- Use the torque wrench to apply counterclockwise torque.
- Carefully remove the barrel nut, ensuring that the wrench remains securely in place to avoid slipping.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding metal waste.
- Do not dispose of the product in household waste.
- If the product is damaged or no longer usable, consider recycling the materials where possible.

Contact Information for Further Support

For any inquiries or concerns regarding the safety or usage of this product, please contact the manufacturer or your point of purchase. Ensure that you have the product details handy for reference.

By following these guidelines, you can help ensure your safety and the effective use of the AR15/M16 URX Barrel Nut Wrench. Thank you for your attention to these important safety instructions.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk