

1911 GRIP BUSHING EXTRACTOR - CHALLIS GRIPS 1911 GRIP BUSHING EXTRACTOR, STANDARD

[Gunsmith Tools](#) > [Handgun Tools](#) > [Grip Tools](#)

Easy & Effective Bushing Removal

Challis bushing extractors are attached to the bushing with a standard grip screw. With the bushing held captive, the drive teeth cannot slip out of engagement and the top of the bushing will not peel off. Significant torque can be applied with the included lever.



Attributes

- Name: [CHALLIS GRIPS 1911 GRIP BUSHING EXTRACTOR, STANDARD](#)
- Manufacturer: [CHALLIS GRIPS](#)
- Product no.: 100017841
- Mfr. No.: T-FBE
- Weapon type: 1911
- Delivery weight: 0.032kg
- Shipping height: 25mm
- Shipping width: 64mm
- Shipping length: 152mm
- UPC: 080687718986

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 1911 Grip Bushing Extractor](#)
- [About Us](#)

Safety Instruction Guide for 1911 Grip Bushing Extractor

Introduction

Thank you for choosing the 1911 Grip Bushing Extractor from Challis Grips. This tool is designed to assist you in the safe and effective removal of standard size or slim 1911 grip bushings. Please read this safety instruction guide carefully to ensure proper usage and to protect yourself while using the product.

General Safety Guidelines

- Always use the tool in accordance with the manufacturer's instructions.
- Keep the tool out of reach of children and vulnerable individuals.
- Inspect the tool before each use to ensure it is in good working condition.
- Report any unsafe products or accidents to the appropriate authorities.
- Check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Ensure the bushing extractor is properly attached to the bushing using the standard grip screw before applying torque.
- Avoid applying excessive force that may lead to tool or bushing damage.
- Use the included lever to apply torque, ensuring a firm grip without slipping.
- Do not attempt to use the extractor on bushings that are not compatible with the tool.
- Always wear appropriate personal protective equipment (PPE), such as safety glasses, while using the tool.

Instructions for Installation and Usage

1. Preparation:

- Ensure the work area is clean and welllit.
- Gather all necessary tools and safety equipment.

2. Attaching the Extractor:

- Align the bushing extractor with the bushing.
- Secure the extractor to the bushing using the standard grip screw. Tighten the screw until the extractor is held firmly in place.

3. Using the Extractor:

- Position the included lever to apply torque.
- Gradually apply torque until the bushing begins to loosen. Monitor the tool and bushing for any signs of slipping or damage.
- If resistance is encountered, reassess the attachment and ensure the extractor is properly engaged before continuing.

4. Removing the Bushing:

- Once the bushing is loosened, carefully remove it from the grip frame.
- Inspect both the bushing and the extractor for any damage after use.

Disposal Instructions

- Dispose of the tool responsibly at a designated electronic waste recycling facility if it becomes damaged beyond repair.
- Follow local regulations for the disposal of tools and any packaging materials.

Contact Information for Further Support

For safety inquiries or additional support regarding the 1911 Grip Bushing Extractor, please refer to the manufacturer's contact details provided with the product packaging or visit the manufacturer's website.

Thank you for your attention to these safety guidelines. Your safety is our priority.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk