

2-CAVITY HANDGUN MOULDS - REDDING 9MM 122GR TRUNCATED CONE MOLD

[Reloading](#) > [Bullet Casting](#) > [Casting Moulds](#) > [Handgun Moulds](#)

All SAEKO moulds are machined from solid cast iron blocks one cavity at a time. Using the same cutting tool (cherrie) for each cavity duplicates the previous one. You don't need to pay a premium for matched cavities. SAEKO even developed its own blend of copper alloyed pearlitic cast iron for tight grain structure, dimensional stability and extended life. The steel sprue plates are held firm against the mould blocks by high-temperature spring washers to insure uniform bullets with square bases.



Attributes

- Name: [REDDING 9MM 122GR TRUNCATED CONE MOLD](#)
- Manufacturer: [REDDING](#)
- Product no.: 100020254
- Mfr. No.: 62377
- Bullet Weight (Grains): 122
- Caliber: 9mm
- Cavities: 2
- Delivery weight: 0.431kg
- Shipping height: 58mm
- Shipping width: 86mm
- Shipping length: 98mm
- UPC: 611760623776

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for 2Cavity Handgun Moulds Redding 9mm 122gr Truncated Cone Mold
- About Us

Safety Instruction Guide for 2Cavity Handgun Moulds Redding 9mm 122gr Truncated Cone Mold

Introduction

Thank you for choosing the 2Cavity Handgun Moulds Redding 9mm 122gr Truncated Cone Mold. This guide provides essential safety instructions to ensure safe usage and compliance with the EU General Product Safety Regulation (GPSR). Please read this guide carefully before using the product.

General Safety Guidelines

- Ensure that the mould is used only for its intended purpose, which is to cast bullets for reloading ammunition.
- Always use the mould in a wellventilated area to avoid inhalation of fumes or dust.
- Keep the mould out of reach of children and vulnerable individuals.
- Regularly inspect the mould for any signs of damage or wear before each use.
- Follow all local laws and regulations regarding the use of reloading equipment and ammunition.

Specific Safety Precautions for Use

- Always wear appropriate personal protective equipment (PPE) including safety glasses, heatresistant gloves, and protective clothing when using the mould.
- Do not exceed the recommended temperature limits when heating the mould to avoid burns or other injuries.
- Ensure that the mould is securely placed on a stable, heatresistant surface during use.
- Avoid touching hot surfaces of the mould to prevent burns.
- If using a heat source, ensure it is stable and does not pose a fire hazard.
- Be aware of the potential for lead exposure when casting bullets; take necessary precautions to minimize exposure.
- Always allow the mould to cool completely before handling or cleaning.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary materials including lead, a heat source, and the mould.
- Ensure your workspace is clean and free of clutter.

2. Setting Up the Mould:

- Place the mould on a stable, heatresistant surface.
- Ensure that the sprue plates are firmly attached to the mould blocks.

3. Heating the Mould:

- Preheat the mould using a suitable heat source until it reaches the recommended temperature.
- Monitor the temperature closely to avoid overheating.

4. Casting Bullets:

- Pour molten lead into the mould cavities carefully, avoiding spills.
- Allow the lead to cool and solidify according to the recommended time.

5. Removing Bullets:

- Once cooled, carefully open the mould and remove the cast bullets.
- Inspect each bullet for quality and consistency.

6. Cleaning the Mould:

- Allow the mould to cool completely before cleaning.
- Use a soft brush or cloth to remove any residue.
- Store the mould in a dry place to prevent rust and damage.

Disposal Instructions

- Dispose of any waste materials, including lead and other casting byproducts, in accordance with local regulations.
- Do not dispose of lead in regular trash; contact local waste management for proper disposal methods.

Contact Information for Further Support

For any safety inquiries or further assistance regarding the 2Cavity Handgun Moulds Redding 9mm 122gr Truncated Cone Mold, please contact your local distributor or manufacturer. Ensure that you have the product details available for reference.

Conclusion

By following these safety instructions, you can ensure a safe and effective experience with your 2Cavity Handgun Moulds Redding 9mm 122gr Truncated Cone Mold. Always prioritize safety and compliance with local regulations when engaging in reloading activities. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk