

TSR PICATINNY SCOPE RINGS - TPS PRODUCTS 1" X-HIGH (1.40") ALUMINUM RINGS

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Super Holding Power, Precision Alignment

TSR Series Rings, precisely machined from an aluminum billet, with tolerances held to .0002", give maximum scope/ring contact. Holds scope securely against recoil. Four-screw cap lets you align the reticle, tighten the left side of the cap, then the right side without the scope rotating. Radiused edges and corners help prevent snagging while providing attractive appearance. Large, clamp-nut lets you torque rings to Mil-STD 1913 (Picatinny) bases.



Attributes

- Name: [TPS PRODUCTS 1" X-HIGH \(1.40"\) ALUMINUM RINGS](#)
- Manufacturer: [TPS PRODUCTS](#)
- Product no.: 100020390
- Mfr. No.: 30523
- Finish: -
- Height: 1.40"
- Material: Aluminum
- Scope Tube Diameter: 1"
- Size: Extra High
- Style: -
- Delivery weight: 0.318kg
- Shipping height: 51mm
- Shipping width: 51mm
- Shipping length: 89mm
- UPC: 071611305235

Item details

Made in USA

Table of Contents

- Startpage
- TSR Picatinny Scope Rings Safety Instructions
- About Us

TSR Picatinny Scope Rings Safety Instructions

Introduction

Thank you for choosing the TSR Picatinny Scope Rings by TPS Products. These aluminum rings are designed to securely hold your scope in place, ensuring optimal performance and safety during use. This guide provides essential safety instructions and guidelines to ensure the safe installation and usage of your scope rings.

General Safety Guidelines

- Always inspect the product before use for any signs of damage or wear.
- Ensure that the scope rings are compatible with your scope and firearm.
- Follow all manufacturer instructions for installation and use.
- Keep the product out of reach of children and vulnerable individuals.
- Store the product in a dry, cool place to prevent corrosion or damage.
- Report any unsafe conditions or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure that the rings are securely tightened to prevent any movement of the scope during use.
- Avoid overtightening, which could damage the scope or rings.
- Always check the alignment of the reticle after installation to ensure proper sighting.
- Be aware of the recoil of your firearm and ensure that the scope rings can withstand this force.
- Use caution when handling firearms equipped with scopes, and always follow firearm safety guidelines.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary tools, including a torque wrench.
- Ensure that your firearm is unloaded and in a safe condition.

2. Installation

- Position the scope in the rings and align it to your desired eye relief.
- Place the ring caps onto the rings, ensuring that they fit securely.
- Using a torque wrench, tighten the screws on the left side of the cap first, followed by the right side. Ensure that the torque applied meets MilSTD 1913 specifications.
- Check the alignment of the reticle and make any necessary adjustments.

3. Usage

- Before firing, doublecheck that the scope is securely mounted and that all screws are tightened.
- After installation, perform a test fire to ensure that the scope holds its zero and remains stable during recoil.

Disposal Instructions

- Dispose of the product in accordance with local regulations for aluminum and other materials.
- Do not dispose of the product in household waste. Consider recycling options where available.

Contact Information for Further Support

For any safety inquiries or concerns regarding the TSR Picatinny Scope Rings, please refer to the manufacturer's contact information provided with your product packaging.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk