

TSR SUPER LOW PICATINNY RINGS - TPS PRODUCTS TSR SUPER LOW ALUMINUM RINGS 30MM

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

TSR SL (Super-Low) Series Rings. Providing an extremely low mounting solution for those special applications. Precisely machined with tolerances held to .0002", give maximum scope/ring contact. Holds scope securely against recoil. Four-screw cap lets you align the reticle, tighten the left side of the cap, then the right side without the scope rotating. Radiused edges and corners help prevent snagging while providing attractive appearance. Large, clamp-nut lets you torque rings to Mil-STD 1913 (Picatinny) bases. Height measured from top of base to center of ring.



Attributes

- Name: [TPS PRODUCTS TSR SUPER LOW ALUMINUM RINGS 30MM](#)
- Manufacturer: [TPS PRODUCTS](#)
- Product no.: 100020397
- Mfr. No.: 32580
- Height: .820"
- Material: Aluminum
- Scope Tube Diameter: 30mm
- Size: Super Low
- Style: -
- Delivery weight: 0.104kg
- Shipping height: 51mm
- Shipping width: 51mm
- Shipping length: 76mm
- UPC: 071611325806

Item details

Made in USA

Table of Contents

- Startpage
- TSR SUPER LOW PICATINNY RINGS Safety Instruction Guide
- About Us

TSR SUPER LOW PICATINNY RINGS Safety Instruction Guide

Introduction

Thank you for choosing the TSR SUPER LOW PICATINNY RINGS by TPS PRODUCTS. These aluminum scope rings are designed to provide a secure and low mounting solution for your optics. This safety instruction guide is intended to ensure safe and effective use of the product in compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Always inspect the product for any visible damage before use.
- Ensure that the installation area is clean and free from obstructions.
- Use the product only for its intended purpose.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe conditions or incidents to the relevant authorities.

Specific Safety Precautions for Use

- Ensure that the scope is compatible with the 30mm diameter of the rings.
- Avoid overtightening the screws, as this may damage the rings or the scope.
- Do not use the rings if they show signs of wear or damage.
- Always check the alignment of the scope before use to ensure proper sighting.
- Handle the product with care to prevent accidental drops or impacts.

Instructions for Installation and Usage

1. Preparation:

- Gather necessary tools, including a torque wrench and appropriate screwdrivers.
- Ensure that the Picatinny base is clean and free from debris.

2. Installation:

- Place the rings onto the Picatinny base, ensuring they are positioned correctly.
- Align the scope within the rings and adjust to the desired position.
- Tighten the left side of the cap first, followed by the right side to prevent rotation of the scope.
- Use a torque wrench to tighten the clampnut according to MilSTD 1913 specifications.

3. Usage:

- After installation, check the stability of the scope and rings before use.
- Regularly inspect the rings during use to ensure they remain secure.
- If any movement or looseness is detected, recheck the installation and tighten as necessary.

Disposal Instructions

- Dispose of the product in accordance with local waste management regulations.
- Recycle aluminum components where possible to minimize environmental impact.

Contact Information for Further Support

For any inquiries regarding safety or product issues, please refer to the manufacturer's website or customer service resources. Ensure you have the product details available for reference.

By following these safety instructions, you can ensure a safe and effective experience with your TSR SUPER LOW PICATINNY RINGS. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk