

TSR SUPER LOW PICATINNY RINGS - TPS PRODUCTS TSR SUPER LOW ALUMINUM RINGS 34MM

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

TSR SL (Super-Low) Series Rings. Providing an extremely low mounting solution for those special applications. Precisely machined with tolerances held to .0002", give maximum scope/ring contact. Holds scope securely against recoil. Four-screw cap lets you align the reticle, tighten the left side of the cap, then the right side without the scope rotating. Radiused edges and corners help prevent snagging while providing attractive appearance. Large, clamp-nut lets you torque rings to Mil-STD 1913 (Picatinny) bases. Height measured from top of base to center of ring.



Attributes

- Name: [TPS PRODUCTS TSR SUPER LOW ALUMINUM RINGS 34MM](#)
- Manufacturer: [TPS PRODUCTS](#)
- Product no.: 100020399
- Mfr. No.: 32595
- Height: .950"
- Material: Aluminum
- Scope Tube Diameter: 34mm
- Size: Super Low
- Delivery weight: 0.154kg
- Shipping height: 57mm
- Shipping width: 57mm
- Shipping length: 95mm
- UPC: 071611325950

Item details

Made in USA

Table of Contents

- Startpage
- TSR SUPER LOW PICATINNY RINGS Consumer Safety Instruction Guide
- About Us

TSR SUPER LOW PICATINNY RINGS Consumer Safety Instruction Guide

Introduction

Thank you for purchasing the TSR SUPER LOW PICATINNY RINGS by TPS PRODUCTS. These rings are designed to provide a secure and low mounting solution for your scope. This guide contains important safety instructions to ensure the safe use of this product, in compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Regularly inspect the rings for signs of wear or damage before each use.
- Keep the product out of reach of children and vulnerable individuals.
- Follow all manufacturer instructions for installation and usage.
- Report any unsafe products or accidents to the relevant authorities.
- Check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Always ensure that the scope is securely mounted in the rings before use.
- Be cautious when tightening screws; overtightening can damage the scope or rings.
- Avoid using the product in extreme environmental conditions (e.g., excessive heat, moisture).
- If the rings become damaged, discontinue use immediately and replace them.
- Do not attempt to modify the rings or their components.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a torque wrench and appropriate screwdrivers.
- Ensure that the mounting surface is clean and free from debris.

2. Installation Steps:

- Position the rings on the Picatinny rail, ensuring they are aligned correctly.
- Loosely attach the rings to the rail using the provided screws.
- Place the scope into the rings and adjust it to the desired position.
- Tighten the left side of the cap first, followed by the right side, ensuring the scope does not rotate during tightening.
- Use the clampnut to torque the rings to the MilSTD 1913 (Picatinny) specifications.

3. Usage:

- Once installed, check the alignment of the scope's reticle.
- Ensure that all screws are securely tightened before using the firearm.
- Regularly check the mounting for stability and tightness during use.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding aluminum and metal waste.
- Do not dispose of the product in regular household waste.
- Consider recycling the product if possible to minimize environmental impact.

Contact Information for Further Support

For any questions or concerns regarding the TSR SUPER LOW PICATINNY RINGS, please refer to the manufacturer's website or customer service for assistance.

Thank you for choosing TPS PRODUCTS. Your safety is our priority.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk