

HRT PICATINNY/WEAVER SCOPE RINGS - TPS PRODUCTS HRT ALUMINUM RINGS 30MM LOW

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Superior Scope-To-Ring Contact With A Slim-Line Look

HRT Series Rings, precisely machined from an alloy steel billet, with tolerances held to .0002", give maximum scope/ring contact. Holds scope securely against recoil. Four-screw cap lets you align the reticle, tighten the left side of the cap, then the right side without the scope rotating. Radiused edges and corners help prevent snagging while providing attractive appearance. Large, clamp-nut lets you torque rings to Weaver-type or Picatinny bases.



Attributes

- Name: [TPS PRODUCTS HRT ALUMINUM RINGS 30MM LOW](#)
- Manufacturer: [TPS PRODUCTS](#)
- Product no.: 100020412
- Mfr. No.: 40580
- Finish: -
- Height: .925"
- Material: Aluminum
- Scope Tube Diameter: 30mm
- Size: Low
- Style: -
- Delivery weight: 0.132kg
- Shipping height: 57mm
- Shipping width: 57mm
- Shipping length: 102mm
- UPC: 071611405805

Item details

Made in USA

Table of Contents

- Startpage
- HRT Picatinny/Weaver Scope Rings Safety Instruction Guide
- About Us

HRT Picatinny/Weaver Scope Rings Safety Instruction Guide

Introduction

Thank you for choosing the HRT Picatinny/Weaver Scope Rings by TPS Products. These rings are designed to provide a secure and stable mounting solution for your scope, ensuring optimal performance during use. This guide outlines important safety instructions and precautions to ensure your safety and the proper functioning of the product.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Regularly inspect the scope rings for signs of wear or damage.
- Always follow manufacturer guidelines for installation and usage.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe products or accidents to the appropriate authorities.
- Check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Recoil Management:** Ensure the scope is securely mounted to prevent movement during recoil.
- **Alignment:** Use the fourscrew cap to align the reticle properly, tightening the left side first, then the right side.
- **Torque Settings:** Use the large clampnut to torque the rings to the appropriate specifications for Weaver type or Picatinny bases.
- **Avoid Snagging:** Be cautious of sharp edges and corners; handle the product with care to avoid injury.
- **Material Handling:** The aluminum material is lightweight but can be damaged; avoid dropping or mishandling.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a torque wrench.
- Ensure the mounting surface is clean and free of debris.

2. Installation:

- Place the scope rings on the Picatinny or Weaver base.
- Align the rings to ensure the scope is level.
- Secure the rings using the screws provided, ensuring they are tightened evenly.

3. Scope Mounting:

- Position the scope within the rings.
- Use the fourscrew cap to secure the scope, aligning the reticle as per the instructions.
- Tighten the screws in the sequence specified: left side first, then right side.

4. Final Checks:

- After installation, doublecheck all screws and fittings to ensure everything is secure.
- Test the scope for stability by simulating recoil.

Disposal Instructions

- Dispose of the product in accordance with local regulations for metal recycling.
- Do not dispose of in regular household waste.
- Ensure that any electronic components (if applicable) are disposed of in accordance with electronic waste regulations.

Contact Information for Further Support

For any inquiries or support related to the HRT Picatinny/Weaver Scope Rings, please refer to the manufacturer's contact details provided on the packaging or the user manual.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk