

RUGER® MARK SERIES "SHADOW" PICATINNY RAIL - TANDEMROSS RUGER MK SERIES "SHADOW" PICATINNY RAIL- BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Provides More Optic Mounting Options - Won't Mess Up Gun's Aesthetics

The Tandemross Shadow Picatinny Rail for Ruger® Mark series and 22/45™ pistols gives you greater flexibility in your choice of optic and in where you position it on your pistol. Eight MIL-STD Picatinny cross-slots give you plenty of leeway in positioning a red dot or other sight for optimal eye relief. Other features of the Shadow Picatinny Rail: Cutout on underside minimizes risk of interference ejected shell casings. Shorter, trimmer & better looking than factory optic rail. Solid & secure - precision-machined aluminum, hardcoat anodized finish. Mounting screws included. Available in Matte Black or Matte Gray to match - or contrast with - your gun's finish. Tandemross designed the Shadow Picatinny Rail so you can install it on your Ruger® Mark series or 22/45™ pistol without removing your gun's "iron" sights. With a quick-release mount on your optic, you can switch back to shooting with iron sights in seconds. The Shadow Picatinny Rail fits factory drilled and tapped receivers on the following Ruger® .22 LR pistols: Mark II™ Mark II™ 22/45™ Mark III™ Mark III™ 22/45™ Mark III™ 22/45™ Lite Mark IV™ Target Mark IV™ Hunter Mark IV™ Competition Mark IV™ 22/45™ Lite



Attributes

- Name: [TANDEMROSS RUGER MK SERIES "SHADOW" PICATINNY RAIL-BLACK](#)
- Manufacturer: [TANDEMROSS](#)
- Product no.: 100025729
- Mfr. No.: TK05N0014BLK1
- Colour: Black
- Material: Aluminum
- Model: 22/45, Mark II, Mark IV, Mark I, Mark III
- Number of Bases: 1-Piece
- Style: Picatinny
- Weapon type: Ruger
- Delivery weight: 0.029kg
- Shipping height: 6mm
- Shipping width: 76mm
- Shipping length: 152mm
- UPC: 091131144244

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for RUGER® MARK SERIES "SHADOW" PICATINNY RAIL
- About Us

Safety Instruction Guide for RUGER® MARK SERIES "SHADOW" PICATINNY RAIL

Introduction

Thank you for choosing the Tandemkross Shadow Picatinny Rail for your Ruger® Mark series or 22/45™ pistol. This guide provides essential safety instructions and information to ensure safe and effective use of the product. Please read this guide carefully before installation and usage.

General Safety Guidelines

- Ensure that the product is suitable for your specific Ruger® model (Mark II™, Mark III™, Mark IV™, or 22/45™).
- Always handle firearms responsibly and in accordance with local laws and regulations.
- Keep the product out of reach of children and unauthorized users.
- Regularly inspect the Picatinny rail for any signs of wear or damage before each use.
- If you encounter any issues during installation or usage, cease use immediately and consult a qualified gunsmith or contact customer support.

Specific Safety Precautions for Use

- Ensure that the firearm is unloaded before attempting to install the Picatinny rail.
- Avoid using the Picatinny rail in wet or damp conditions, as this may affect the integrity of the rail and the optic mounted on it.
- Do not exceed the weight limit of the rail when mounting optics or accessories to prevent failure.
- When switching between optics and iron sights, ensure the firearm is pointed in a safe direction and the safety is engaged.
- Do not modify the Picatinny rail or the firearm in any way that could compromise safety.

Instructions for Installation and Usage

1. Preparation:

- Ensure your Ruger® Mark series or 22/45™ pistol is unloaded and pointed in a safe direction.
- Gather necessary tools for installation, including a screwdriver suitable for the mounting screws provided.

2. Installation:

- Locate the factory drilled and tapped receiver on your Ruger® pistol.
- Align the Tandemkross Shadow Picatinny Rail with the mounting holes.
- Insert the mounting screws provided with the rail into the aligned holes and tighten securely, ensuring the rail is stable and does not move.

3. Optic Mounting:

- Attach your chosen optic to the Picatinny rail using the appropriate mounting hardware.
- Adjust the position of the optic to achieve optimal eye relief while ensuring it does not interfere with the firearm's iron sights.

4. Final Check:

- After installation, doublecheck that all screws are tightened and that the optic is securely mounted.

- Perform a function check on your firearm to ensure it operates correctly with the new rail and optic.

Disposal Instructions

- Dispose of any packaging materials in accordance with local waste disposal regulations.
- If the product reaches the end of its useful life, dispose of it in a manner that complies with local environmental regulations, ensuring that it does not pose a risk to the environment or public safety.

Contact Information for Further Support

For any questions or concerns regarding the Tandemkross Shadow Picatinny Rail, please refer to the manufacturer's website or consult with a qualified gunsmith.

Conclusion

Following these safety instructions will help ensure a safe and enjoyable experience with your Tandemkross Shadow Picatinny Rail. Always prioritize safety and responsibility when handling firearms and associated accessories. Thank you for your attention to these guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk