

AR-15 DOUBLE TUNGSTEN H2 BUFFER - LUTH-AR AR-15 DOUBLE TUNGSTEN H2 BUFFER

[Rifle Parts](#) > [Receiver Parts](#) > [Recoil Parts](#) > [Recoil Buffers](#)

Luth-AR factory replacement Double Tungsten H2 Buffer. Fits standard AR-15 rifles.



Attributes

- Name: [LUTH-AR AR-15 DOUBLE TUNGSTEN H2 BUFFER](#)
- Manufacturer: [LUTH-AR](#)
- Product no.: 100028019
- Mfr. No.: CS-T2
- Weapon type: AR-15
- Delivery weight: 0.136kg
- Shipping height: 25mm
- Shipping width: 25mm
- Shipping length: 76mm
- UPC: 859819007218

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- Startpage
- Safety Instruction Guide for AR15 Double Tungsten H2 Buffer
- About Us

Safety Instruction Guide for AR15 Double Tungsten H2 Buffer

Introduction

Thank you for choosing the LuthAR Double Tungsten H2 Buffer for your AR15 rifle. This guide provides essential safety instructions and usage guidelines to ensure the safe operation of your product. Please read this manual carefully before installation and usage.

General Safety Guidelines

- Ensure that the buffer is compatible with your specific AR15 model.
- Always handle firearms in a safe manner, following basic firearm safety rules.
- Store the buffer and all firearm components in a secure location, away from children and unauthorized users.
- Regularly inspect the buffer for signs of wear or damage before each use.
- Be aware of the legal requirements and regulations regarding firearm modifications in your jurisdiction.

Specific Safety Precautions for Use

- Use the buffer only as intended and in accordance with the manufacturer's specifications.
- Do not exceed the recommended weight limits for the buffer.
- Avoid using the buffer with ammunition that exceeds the manufacturer's guidelines.
- If you experience any unusual sounds or malfunctions during use, cease operation immediately and consult a qualified gunsmith.
- Keep your hands and body clear of the buffer when the firearm is in use to avoid injury.

Instructions for Installation and Usage

1. Preparation

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather the necessary tools for installation, including a wrench and any other required tools.

2. Installation Steps

- Remove the existing buffer from the buffer tube by unscrewing it counterclockwise.
- Inspect the buffer tube for any debris or damage.
- Take the LuthAR Double Tungsten H2 Buffer and align it with the buffer tube.
- Screw the buffer into the buffer tube clockwise until secure.
- Ensure that the buffer moves freely within the buffer tube.

3. Usage Guidelines

- After installation, conduct a function check to ensure that the buffer operates correctly with your AR15 rifle.
- Fire the rifle in a controlled environment, observing all safety protocols.
- Monitor the performance of the buffer during use and be vigilant for any signs of malfunction.

Disposal Instructions

- Dispose of the buffer in accordance with local regulations regarding firearm components.
- Do not dispose of the buffer in regular household waste.

- Contact local authorities or a licensed firearms dealer for guidance on proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the LuthAR Double Tungsten H2 Buffer, please refer to the manufacturer's contact information provided in the product packaging or visit the official website.

Thank you for prioritizing safety and compliance while using the LuthAR Double Tungsten H2 Buffer. By following these guidelines, you contribute to a safer experience in firearm usage.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk