

2 CAVITY PISTOL BULLET MOLDS - LEE PRECISION 45 CALIBER (0.452") 160GR ROUND NOSE MOLD

[Reloading](#) > [Bullet Casting](#) > [Casting Moulds](#) > [Handgun Moulds](#)

All molds for pistol calibers are double cavity to speed casting. All Lee mould blocks are made from aluminum because of the exceptional moulding qualities. The mould cavities are CNC machined for unmatched roundness and size control. Most bullets from Lee moulds can be used as cast without sizing. Handles and sprue plate are included.



Attributes

- Name: [LEE PRECISION 45 CALIBER \(0.452"\) 160GR ROUND NOSE MOLD](#)
- Manufacturer: [LEE PRECISION](#)
- Product no.: 100032158
- Mfr. No.: 90570
- Bullet Weight (Grains): 160
- Caliber: 45 Caliber
- Cavities: 2
- Diameter (in): 0.452
- Delivery weight: 0.386kg
- Shipping height: 51mm
- Shipping width: 76mm
- Shipping length: 279mm
- UPC: 734307905705

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for 2 Cavity Pistol Bullet Molds by Lee Precision
- About Us

Safety Instruction Guide for 2 Cavity Pistol Bullet Molds by Lee Precision

Introduction

Thank you for choosing the 2 Cavity Pistol Bullet Molds by Lee Precision. This guide provides essential information on the safe use, installation, and disposal of your bullet molds to ensure your safety and compliance with EU regulations.

General Safety Guidelines

- Always read and understand the instructions before using the product.
- Keep the product out of reach of children and vulnerable individuals.
- Use the product only for its intended purpose.
- Regularly inspect the molds for any signs of damage or wear.
- Report any unsafe product conditions or accidents to the appropriate authorities.
- Stay informed about product recalls by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Handle the molds with care to avoid injury from sharp edges.
- Ensure that the molds are used in a wellventilated area to prevent inhalation of fumes.
- Wear appropriate personal protective equipment (PPE), such as gloves and safety glasses, when casting bullets.
- Avoid contact with hot surfaces to prevent burns.
- Do not exceed the recommended temperature limits when using the molds.
- Ensure that the casting area is clean and free from flammable materials.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary materials: bullet lead, a heat source, and personal protective equipment.
- Ensure that your work area is clean and wellventilated.

2. Setting Up the Molds

- Place the bullet molds on a stable, heatresistant surface.
- Ensure that the sprue plate is properly aligned and secured.

3. Casting Bullets

- Heat the molds to the recommended temperature before pouring lead.
- Carefully pour the molten lead into the mold cavities, ensuring not to overfill.
- Allow the lead to cool and solidify before removing the bullets.

4. Removing Bullets

- Once cooled, gently open the molds and remove the bullets.
- Inspect the bullets for any defects or irregularities.

5. Cleaning and Maintenance

- Clean the molds after each use to prevent lead buildup.

- Store the molds in a dry place to avoid corrosion.

Disposal Instructions

- Dispose of any lead waste according to local regulations.
- Do not dispose of the molds in regular household waste; check for recycling options in your area.
- Follow local guidelines for the safe disposal of hazardous materials.

Contact Information for Further Support

For any safety inquiries or additional support, please refer to your local EU contact point or the manufacturer's website for assistance.

By following these guidelines, you can ensure a safe and effective experience with your Lee Precision 2 Cavity Pistol Bullet Molds. Thank you for your attention to safety!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk