

417S SINGLE PORT COMPENSATOR - 417S SINGLE PORT COMP FOR GLOCK® GEN 4, BLK, 9MM

[Handgun Parts](#) > [Barrel Parts](#) > [Muzzle Devices](#) > [Compensators](#)

The Agency Arms 417 Compensator is threaded with the standard 1/2x28 thread pitch. It features a single top venting port and it also features a front sight hole. It is designed to utilize the OEM recoil spring assembly and the front sight hole allows you to transfer your existing front sight from your slide to the comp. Compatible with the 17,19 and 34 Includes: Comp 2 Set Screws



Attributes

- Name: [417S SINGLE PORT COMP FOR GLOCK® GEN 4, BLK, 9MM](#)
- Manufacturer: [AGENCY ARMS](#)
- Product no.: 100033473
- Mfr. No.: 417S-G4-BLK
- Make: Glock
- Model: 17,19,19X,26,34,45
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 25mm
- Shipping length: 25mm

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 417S Single Port Compensator](#)
- [About Us](#)

Safety Instruction Guide for the 417S Single Port Compensator

Introduction

Thank you for choosing the Agency Arms 417S Single Port Compensator for your Glock® Gen 4. This guide provides essential safety instructions and information to ensure the safe use and installation of your compensator. Please read this manual thoroughly before use.

General Safety Guidelines

- Ensure that the compensator is compatible with your specific Glock® model (17, 19, 34, 26, 45, 19X).
- Always handle firearms with care and follow all safety protocols.
- Use the compensator only as intended and according to the instructions provided.
- Keep the compensator and all firearm accessories out of reach of children and unauthorized users.
- Regularly inspect the compensator for signs of wear or damage before each use.
- Report any unsafe products or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Always wear appropriate eye protection when using firearms equipped with the compensator.
- Ensure the firearm is unloaded before installing or removing the compensator.
- Do not modify the compensator or firearm in any way that could compromise safety or performance.
- Avoid using the compensator with ammunition that exceeds the specified caliber (9MM).
- Be aware of the potential for increased noise and muzzle blast when using the compensator.

Instructions for Installation and Usage

1. Installation

- Ensure the firearm is unloaded.
- Remove the existing muzzle device from your Glock®.
- Thread the 417S compensator onto the barrel using the standard 1/2x28 thread pitch.
- Secure the compensator in place with the included set screws.
- Transfer your existing front sight to the compensator's front sight hole if applicable.

2. Usage

- Always check that the compensator is securely attached before each use.
- Fire the firearm in a safe and controlled environment.
- Monitor for any unusual performance or behavior during use.

Disposal Instructions

- Dispose of the compensator in accordance with local regulations.
- Do not dispose of the compensator in regular household waste.
- Contact your local waste management authority for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the Agency Arms 417S Single Port Compensator, please consult the manufacturer's website or contact their customer support directly.

By following these safety instructions and guidelines, you can ensure a safe and enjoyable experience with your Agency Arms 417S Single Port Compensator. Thank you for your attention to safety.

About Us

Brownells Austria

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.at