

417S SINGLE PORT COMPENSATOR - AGENCY ARMS 417S SINGLE PORT COMP FOR GLOCK® GEN 4, GOLD, 9MM

[Handgun Parts](#) > [Barrel Parts](#) > [Muzzle Devices](#) > [Compensators](#)

The Agency Arms 417 Compensator is threaded with the standard 1/2x28 thread pitch. It features a single top venting port and it also features a front sight hole. It is designed to utilize the OEM recoil spring assembly and the front sight hole allows you to transfer your existing front sight from your slide to the comp. Compatible with the 17,19 and 34 Includes: Comp 2 Set Screws



Attributes

- Name: [AGENCY ARMS 417S SINGLE PORT COMP FOR GLOCK® GEN 4, GOLD, 9MM](#)
- Manufacturer: [AGENCY ARMS](#)
- Product no.: 100033474
- Mfr. No.: 417S-G4-GLD
- Model: 17,19,19X,26,34,45
- Weapon type: Glock
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 25mm
- Shipping length: 25mm

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- [Startpage](#)
- [Agency Arms 417S Single Port Compensator Safety Instruction Guide](#)
- [About Us](#)

Agency Arms 417S Single Port Compensator

Safety Instruction Guide

Introduction

Thank you for purchasing the Agency Arms 417S Single Port Compensator for Glock® Gen 4. This guide provides essential safety instructions and information to ensure the safe and effective use of your compensator. Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure that the compensator is compatible with your Glock model (17, 19, 34, 26, 45, 19X).
- Always handle firearms with care and follow all applicable laws and regulations.
- Store the compensator and firearm in a safe location, out of reach of children and unauthorized users.
- Regularly inspect the compensator for any signs of wear or damage before use.
- Report any unsafe products or incidents to the appropriate authorities.
- Stay informed about product recalls by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Always use appropriate personal protective equipment (PPE) such as safety glasses and hearing protection when using your firearm with the compensator.
- Ensure that the firearm is unloaded and pointed in a safe direction before installation.
- Avoid using the compensator if it shows any signs of damage or if it does not fit securely on your firearm.
- Do not modify the compensator or firearm in any way that may affect safety or performance.
- Be aware of the increased noise and muzzle blast that may result from using a compensator.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Remove the existing front sight from your slide.
- Align the compensator with the threaded barrel and screw it on securely using the standard 1/2x28 thread pitch.
- Use the included set screws to secure the compensator in place.
- Reinstall the front sight into the front sight hole of the compensator.

2. Usage:

- After installation, perform a function check to ensure the compensator is securely attached and that the firearm operates correctly.
- Always follow safe shooting practices and be aware of your surroundings when using your firearm.
- Regularly clean and maintain the compensator and firearm to ensure optimal performance.

Disposal Instructions

- Dispose of the compensator in accordance with local regulations regarding electronic and nonelectronic waste.
- Do not dispose of the compensator in household waste. Check with local waste management facilities for proper disposal methods.

Contact Information for Further Support

For further assistance or inquiries regarding the Agency Arms 417S Single Port Compensator, please refer to the manufacturer's contact information found on the packaging or official website.

Thank you for choosing Agency Arms. Your safety is our priority.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk