

AMBI QD SLING MOUNT - KINETIC RESEARCH GROUP WHISKEY-3, X-RAY, BRAVO AMBI QD SLING MOUNT

[Shooting Accessories](#) > [Slings & Sling Swivels](#) > [Tactical Sling Mounts](#)

With This Sling Mount Your Sling Will Stay Put

Ambi Sling Mount mount seats into the front of your KRG chassis and provides a non-rotational QD mounting point on either side of the forend and also one at the bottom position. You can also use HK type hooks with this mount. Fits: All Whiskey-3 Chassis, all X-ray Chassis, Bravo Chassis, and TRG-22/42.

Restrictions: Requires removal of steel insert plate on TRG's, can't use TRG bipod, cannot be used in conjunction with KRG Spigot Mount.



Attributes

- Name: [KINETIC RESEARCH GROUP WHISKEY-3, X-RAY, BRAVO AMBI QD SLING MOUNT](#)
- Manufacturer: [KINETIC RESEARCH GROUP](#)
- Product no.: 100033849
- Mfr. No.: AMB-QDM
- Colour: Black
- Delivery weight: 0.136kg
- Shipping height: 25mm
- Shipping width: 102mm
- Shipping length: 229mm

Item details

Made in USA

AMBI QD Sling Mount Safety Instruction Guide

Introduction

Thank you for choosing the AMBI QD Sling Mount from Kinetic Research Group. This guide provides important safety instructions and usage information to ensure your product is used safely and effectively.

General Safety Guidelines

- Ensure that the AMBI QD Sling Mount is installed correctly to prevent accidents.
- Always inspect the sling mount before use for any signs of wear or damage.
- Keep the product out of reach of children and vulnerable individuals.
- Use the sling mount only with compatible chassis as specified in the product description.
- Report any unsafe conditions or accidents to the relevant authorities.

Specific Safety Precautions for Use

- The AMBI QD Sling Mount is designed for use with the following chassis:
 - All Whiskey3 Chassis
 - All Xray Chassis
 - Bravo Chassis
 - TRG22/42
- Do not attempt to use the sling mount with incompatible products.
- Removal of the steel insert plate on TRG chassis is required for installation. Ensure this is done safely.
- The TRG bipod cannot be used in conjunction with this sling mount.
- HK type hooks can be used with this mount; ensure they are compatible and in good condition.

Instructions for Installation and Usage

1. Installation:

- Begin by removing the steel insert plate from the TRG chassis if applicable.
- Align the AMBI QD Sling Mount with the designated mounting points on the chassis.
- Securely fasten the mount using the provided hardware, ensuring it is tight and stable.
- Confirm that the mount is nonrotational and properly seated.

2. Usage:

- Attach your sling to the QD mounting points on either side of the forend and at the bottom position.
- Ensure that all connections are secure before use.
- Regularly check the mount for any signs of wear or loosening during use.

Disposal Instructions

- Dispose of the AMBI QD Sling Mount in accordance with local regulations.
- If the product is damaged or no longer in use, do not discard in regular waste. Check for recycling options in your area.

Contact Information for Further Support

For any questions or concerns regarding the AMBI QD Sling Mount, please refer to your retailer or manufacturer's website for contact details and support options.

By following these guidelines, you can ensure the safe and effective use of your AMBI QD Sling Mount. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk