

XRT X-RINGS PICATINNY SCOPE RINGS - TPS PRODUCTS XRT ALUMINUM RINGS 30MM HIGH

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

XRT Series X-Rings, bringing a whole new level of beauty and precision into an extremely rugged Picatinny platform scope mount. The X-Rings have been built from the bottom up to provide the extreme precision and accuracy that TPS rings have been known for over the last two decades. The ring bases begin from a solid billet of 7075-T6 aluminum and then machined with our unique Double-Lug Picatinny recoil shoulders from the solid billet. We have designed and engineered the Double-Lug recoil system to allow the parallelism and perpendicularity of the lugs to the ring bore to be within .0002, thereby providing repeatability that no other mount in the world with similar integrated lugs has done before. The X-Rings are specifically designed for the Mil-STD 1913 rail system. Because of the Double-Lug system, they do require two (2) accompanied cross-slots in a 1913 cross-slot configuration. The ring caps are secured with Four (4) 8-32 x 1/2" Camcar-Textron Torx drive screws and with the same unique design that allows you to tighten the left side of the cap, then the right side without the scope rotating. The edges and corners are fully radiused, preventing snagging, and providing a beautiful appearance to your rifle. The rings are securely attached to your rail with an oversized clamp system using Two (2) 8-32 x 1/2" Camcar-Textron Torx screws, preventing any chance your rings will loosen or move once installed. With unparalleled precision and holding force, and sleek design, these will meet the extreme expectations of any class shooter. SPECS: 7075-T651 Aluminum Alloy, matte black, hard anodized to Mil-A-8625 standards. .700" (17.8mm) wide. Height measured from the top of base to center of the ring. 30mm - High: .1.075" (31.11mm).



Attributes

- Name: [TPS PRODUCTS XRT ALUMINUM RINGS 30MM HIGH](#)
- Manufacturer: [TPS PRODUCTS](#)
- Product no.: 100036963
- Mfr. No.: 50582
- Finish: Matte Blue
- Height: 1.225"
- Material: Aluminum
- Scope Tube Diameter: 30mm
- Size: High
- Style: Tactical Rings
- Delivery weight: 0.181kg
- Shipping height: 64mm
- Shipping width: 64mm
- Shipping length: 127mm
- UPC: 071611505826

Item details

Made in USA

Table of Contents

- Startpage
- XRT XRINGS PICATINNY SCOPE RINGS Safety Instruction Guide
- About Us

XRT XRINGS PICATINNY SCOPE RINGS Safety Instruction Guide

Introduction

Thank you for choosing the XRT XRings Picatinny Scope Rings by TPS Products. These rings are designed to provide exceptional precision and security for your scope. This safety instruction guide is designed to ensure your safe use of the product in compliance with the EU General Product Safety Regulation (GPSR). Please read this guide carefully before installation and use.

General Safety Guidelines

- Ensure that the product is suitable for your specific scope and firearm.
- Always inspect the scope rings for any signs of damage or wear before use.
- Keep the product out of reach of children and vulnerable individuals.
- Follow all local laws and regulations regarding firearm accessories.
- In case of any incidents or malfunctions, report them to the relevant authorities.
- Regularly check for product recalls on the EU Safety Gate platform.

Specific Safety Precautions for Use

• Installation Safety:

- Always ensure the firearm is unloaded before installing or adjusting the scope rings.
- Use appropriate tools as specified for installation to prevent damage to the rings or firearm.

• Usage Safety:

- Do not exceed the recommended torque specifications when securing the rings to avoid damage.
- Regularly check the tightness of the screws to ensure the rings remain securely attached.

• Handling Safety:

- Handle the scope and rings with care to avoid dropping or damaging them.
- Ensure that the scope is properly aligned and secured within the rings before use.

• Environmental Safety:

- Avoid exposing the rings to extreme temperatures or corrosive environments that may compromise integrity.
- Store the product in a dry and cool place when not in use.

Instructions for Installation and Usage

1. Installation Instructions:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Place the XRT XRings onto the Picatinny rail, ensuring that the DoubleLug system aligns with the crossslots on the rail.
- Secure the rings using Two (2) 832 x 1/2" CamcarTextron Torx screws, tightening them evenly to ensure stability.
- Attach the scope into the rings, ensuring it is properly seated and aligned.
- Secure the ring caps using Four (4) 832 x 1/2" CamcarTextron Torx drive screws, tightening the left

side first, followed by the right side to prevent rotation of the scope.

2. Usage Instructions:

- After installation, check the alignment of the scope and make adjustments as necessary.
- Use the firearm in a safe and controlled environment, following all safety protocols.
- Regularly inspect the scope rings and screws for any signs of wear or loosening.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding metal and aluminum waste.
- Do not dispose of the product in regular household waste.
- Consider recycling the aluminum components if possible.

Contact Information for Further Support

For any questions or concerns regarding the XRT XRings Picatinny Scope Rings, please refer to the manufacturer's website or contact the appropriate support channels. Always ensure you have the model number and purchase information available for assistance.

Thank you for your attention to these safety instructions. Your safety and satisfaction are our top priorities. Enjoy your shooting experience with the XRT XRings!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk