

SLING STUD QUICK DETACH BIPODS - MAGPUL QD SLING STUD BIPOD BLACK

[Shooting Accessories](#) > [Bipods, Monopods & Accessories](#) > [Bipods](#)

The Magpul Bipod - Sling Stud QD offers serious strength and versatility at a price that provides unmatched value. Magpul's lightweight Mil-Spec hard anodized 6061 T-6 aluminum and injection-molded polymer bipod brings innovation in ergonomics, functionality, strength and value together. Its low-profile design conceals its internal mechanisms and hardware, smoothly brushing off snags and bumps. Optimized for rapid one-handed adjustments, the bipod quickly and quietly transitions between user configurations.

Designed to mount to the popular Uncle Mike's-style sling swivel stud, the Magpul Bipod - Sling Stud QD attaches and detaches quickly and easily thanks to its rapid-attach mounting system. The self-locating, stainless-steel clasps ensure perfect alignment when mounting, and the non-marring, rubber saddle fits securely on most forends, providing ideal load distribution without leaving a mark on your rifle. In the shooting position, it is easily loaded with stabilizing forward tension without fear of failure or warping. Its aluminum and stainless steel components, along with its injection-molded reinforced polymer, ensure years of dependable performance and reliability, all while shaving weight. It's extremely light weight, at just 13 oz. Leg extensions slide and lock securely with the push of a button on any of the seven half-inch spaced locking detents. The legs extend 3.5 inches, from 6.8" to 10.3". An industry-exclusive 50° of total tilt is controlled by a glove-friendly knurled tool-less bipod locking knob located between the extended legs. Folded, the streamlined housing and legs fit neatly under the barrel and are just under 2.3" deep and 3.3" wide. Anodized surfaces and tight, precision tolerances mitigate squeaks and rattles. A soft rubber cap attached to the aluminum locking knob gives users a steady, non-marring forward rest while the bipod is folded. Additionally, its staggered soft rubber feet hold fast on a variety of shooting surfaces and are easily removed with a roll pin punch. Should users choose to change feet, the Magpul Bipod's legs accept most Atlas pattern bipod replaceable feet, except for the Atlas 5-H style. Made in the USA. FEATURES Designed for streamlined storage until deployment Folded, the sleek housing and legs fit neatly under the barrel and are just under 2.3" deep and 3.3" wide Leg extensions slide and lock securely with the push of a button and a tool-less knurled bipod locking knob allows easy adjustment between shots Legs extend from 6.8" to 10.3" with seven locking detents Spring-tensioned legs stow forward when not in use, and then quickly snap down and lock into place with one hand Legs accept most Atlas pattern bipod replaceable feet to best match the needs of your environment SPECS Attachment: Sling Stud Materials: Steel, Mil-Spec hard anodized 6061 T-6 aluminum, polymer Height, max: 10.0 in. Pan and Tilt: 50° tilt Weight: 13 oz.

The Magpul Bipod is optimized for rapid one-handed adjustments. This bipod can be quickly and quietly transitioned between an almost endless variety of user configurations. And it's built to last, too. Constructed of hardcoat anodized 6061 T6 aluminum, with stainless steel internals, and injection-molded reinforced polymer components to ensure years of dependable service - all while keeping weight to a minimum. The result is a strong, lightweight (11 oz. all up!), versatile bipod that's available in four models set up to mount quickly to the four most popular attachment systems: the classic MIL-STD 1913 Picatinny rail, Magpul's own innovative M-LOK® system, the popular



A.R.M.S. 17S attachment interface, and a standard QD Sling Swivel Stud. The Magpul Bipod features spring-tensioned legs that stow neatly forward and snap down and lock in place quickly when needed. At the push of a button, the legs extend a generous four inches, from 6.3" to 10.3", and lock securely at any one of the seven 1/2"-spaced locking detents. Magpul provides an industry-exclusive 50° of total tilt and 40° of total pan controlled by the glove-friendly knurled bipod locking knob - no tool required - that enables fast, easy adjustment between shots. Additionally, the Magpul Bipod has the exclusive ability to lock pan at 0°, while maintaining full tilt functionality. Wide range of FAST adjustability Rugged aluminum, steel & reinforced polymer construction Available in Black or Flat Dark Earth (FDE) Available in FOUR mounting configurations: MIL-STD 1913 Picatinny, M-LOK®, A.R.M.S 17S, QD Sling Swivel Stud Only 11 oz. to 13 oz. wt. (depending on mounting system) A soft rubber cap on the bipod's locking knob gives the user a steady, non-marring forward rest for shooting when the bipod is folded. Additionally, this 'pod's soft rubber feet hold fast on a variety of shooting surfaces, and they're easily removed with a roll pin punch. If you want to change the feet, the Magpul Bipod's legs accept all Atlas-pattern bipod replaceable feet (except Atlas 5-H style).

Attributes

- Name: [MAGPUL QD SLING STUD BIPOD BLACK](#)
- Manufacturer: [MAGPUL](#)
- Product no.: 100039308
- Mfr. No.: MAG1075-BLK
- Attachment: QD Sling Swivel
- Colour: Black
- Feet Material: Rubber
- Folding: Yes
- Height: 6.7 to 10
- Style: Swivel
- Weight: 13.0 oz
- Delivery weight: 0.481kg
- Shipping height: 76mm
- Shipping width: 102mm
- Shipping length: 241mm
- UPC: 840815123071

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for SLING STUD QUICK DETACH BIPODS MAGPUL QD SLING STUD BIPOD BLACK
- About Us

Safety Instruction Guide for SLING STUD QUICK DETACH BIPODS MAGPUL QD SLING STUD BIPOD BLACK

Introduction

Thank you for choosing the SLING STUD QUICK DETACH BIPODS MAGPUL QD SLING STUD BIPOD BLACK. This guide provides essential safety information and instructions to ensure safe and effective use of your bipod. Please read this guide carefully before use.

General Safety Guidelines

- Ensure that the bipod is used in accordance with all local laws and regulations.
- Always inspect the bipod before use for any signs of damage or wear.
- Keep the bipod out of reach of children and unauthorized users.
- Use the bipod only for its intended purpose: stabilizing firearms during shooting.
- Avoid using the bipod in adverse weather conditions that may affect its functionality.
- Do not exceed the weight limit specified by the manufacturer when using the bipod.

Specific Safety Precautions for Use

- Before adjusting the bipod, ensure that your firearm is unloaded and pointed in a safe direction.
- When extending the legs, do so slowly and with control to prevent accidental injury.
- Always lock the legs in place after adjusting their length to prevent accidental collapse.
- When transitioning between different mounting systems, ensure compatibility to avoid malfunctions.
- Be aware of your surroundings and ensure that the area is clear of obstacles and bystanders before shooting.

Instructions for Installation and Usage

1. Installation

- Ensure that the bipod is compatible with your firearm's attachment system (MILSTD 1913 Picatinny, MLOK®, A.R.M.S 17S, or QD Sling Swivel Stud).
- Align the bipod with the attachment point on your firearm.
- Securely fasten the bipod using the appropriate method for the attachment system.
- Doublecheck that the bipod is firmly attached before use.

2. Usage

- To deploy the bipod, press the release button and extend the legs to the desired length.
- Lock the legs in place by ensuring they snap securely into the locking detents.
- Adjust the tilt and pan of the bipod using the knurled locking knob for optimal positioning.
- When finished, fold the bipod legs forward for storage.

Disposal Instructions

- Dispose of the bipod in accordance with local waste management regulations.
- If the bipod is damaged beyond repair, ensure that it is disposed of safely to prevent accidents.
- Recycle materials where possible, following local recycling guidelines.

Contact Information for Further Support

For any safety inquiries or support regarding the SLING STUD QUICK DETACH BIPODS MAGPUL QD SLING STUD BIPOD BLACK, please refer to the manufacturer's contact details provided with the product packaging.

Conclusion

By following these safety guidelines and instructions, you can ensure a safe and enjoyable experience with your bipod. Always prioritize safety and responsible usage to protect yourself and others. Thank you for choosing Magpul.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk