

OFFSET OPTIC MOUNT - ARISAKA DEFENSE PLATE #7 TALL HEIGHT (1.9"-2.2") OPTIC PLATE

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The Patent Pending Arisaka Offset Optic Mount is a modular mounting solution that allows the user to select a 35 or 45 degree offset position for a red dot sight without requiring additional components. The 35 degree position brings the red dot sight up closer to slimmer, smaller scopes, while the 45 degree position provides additional clearance around wider turrets or larger, higher magnification scopes. The Arisaka Offset Optic Mount is designed to be attached to the top Picatinny rail of an AR15 rifle. When the rifle is canted to make use of the offset red dot sight, the optic remains centered over the bore and maintains a lower 1/3 co-witness height. The base and optic plates can be reversed, allowing for use on the left or right side. The base and plates can each be purchased separately or as a combination, providing an upgrade path in the future as users acquire new red dot sights. Weight: 1.9 oz without optic. Length: 1.0" for the base, which occupies three Picatinny slots (twin recoil lugs and clamping screw). Height: The base sits 0.180" above the surface of the Picatinny rail. The mount is CNC machined from 6061-T6 aluminum and MIL-A-8625 Type III hard coat anodized. IP20 and IP27 Torx Plus bit drivers are included with each base. Standard height (for 1.5" to 1.8" scope mounts): Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 6: Aimpoint Acro Tall height (1.9" to 2.2" scope mounts): Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 12: Aimpoint Acro



Attributes

- Name: [ARISAKA DEFENSE PLATE #7 TALL HEIGHT \(1.9"-2.2"\) OPTIC PLATE](#)
- Manufacturer: [ARISAKA DEFENSE](#)
- Product no.: 100040228
- Mfr. No.: OOM-P7
- Bullet Style: -
- Caliber: -
- Colour: Black
- Diameter (in): -
- Fits / Used For: -
- Grain: -
- Material: Aluminum
- Number of Bases: 1-Piece
- Style: Offset
- Delivery weight: 0.041kg
- Shipping height: 25mm
- Shipping width: 57mm
- Shipping length: 108mm

- UPC: 601557939777

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #7 TALL HEIGHT (1.9"2.2") OPTIC PLATE
- About Us

Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #7 TALL HEIGHT (1.9"2.2") OPTIC PLATE

Introduction

Thank you for choosing the OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #7 TALL HEIGHT. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your optic mount. Please read this document carefully before installation and use.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose as described in this guide.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the mount for any signs of wear or damage before each use.
- If you notice any defects or irregularities, cease use immediately and consult a professional.
- Follow all local laws and regulations regarding firearm accessories.

Specific Safety Precautions for Use

- Use the optic mount only with compatible red dot sights as specified in the product description.
- Ensure that the mount is securely attached to the Picatinny rail before each use.
- Avoid using excessive force when tightening screws to prevent damage to the mount or firearm.
- Never attempt to modify or alter the mount in any way.
- Be aware of your surroundings and ensure a safe environment when using firearms equipped with this mount.

Instructions for Installation and Usage

1. Installation

- Gather necessary tools: IP20 and IP27 Torx Plus bit drivers (included).
- Ensure the firearm is unloaded and pointed in a safe direction.
- Clean the Picatinny rail area where the mount will be attached.
- Align the base of the optic mount with the desired position on the Picatinny rail.
- Secure the mount using the provided screws, ensuring it is firmly in place.

2. Usage

- When using the offset red dot sight, ensure the rifle is canted to the appropriate angle for optimal sight alignment.
- Confirm that the optic remains centered over the bore and maintains a lower 1/3 cowitness height.
- Adjust the mount as needed for left or right side usage by reversing the base and optic plates.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling options for aluminum components where available.

Contact Information for Further Support

For any inquiries regarding safety or product usage, please refer to the manufacturer's contact points provided with your purchase.

Conclusion

By following these safety instructions, you can ensure a safe and effective experience with your OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #7 TALL HEIGHT. Always prioritize safety and compliance with local laws when using firearm accessories. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk