

OFFSET OPTIC MOUNT - ARISAKA DEFENSE PLATE #12 TALL HEIGHT (1.9"-2.2") OPTIC PLATE

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The Patent Pending Arisaka Offset Optic Mount is a modular mounting solution that allows the user to select a 35 or 45 degree offset position for a red dot sight without requiring additional components. The 35 degree position brings the red dot sight up closer to slimmer, smaller scopes, while the 45 degree position provides additional clearance around wider turrets or larger, higher magnification scopes. The Arisaka Offset Optic Mount is designed to be attached to the top Picatinny rail of an AR15 rifle. When the rifle is canted to make use of the offset red dot sight, the optic remains centered over the bore and maintains a lower 1/3 co-witness height. The base and optic plates can be reversed, allowing for use on the left or right side. The base and plates can each be purchased separately or as a combination, providing an upgrade path in the future as users acquire new red dot sights. Weight: 1.9 oz without optic. Length: 1.0" for the base, which occupies three Picatinny slots (twin recoil lugs and clamping screw). Height: The base sits 0.180" above the surface of the Picatinny rail. The mount is CNC machined from 6061-T6 aluminum and MIL-A-8625 Type III hard coat anodized. IP20 and IP27 Torx Plus bit drivers are included with each base. Standard height (for 1.5" to 1.8" scope mounts): Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 6: Aimpoint Acro Tall height (1.9" to 2.2" scope mounts): Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 12: Aimpoint Acro



Attributes

- Name: [ARISAKA DEFENSE PLATE #12 TALL HEIGHT \(1.9"-2.2"\) OPTIC PLATE](#)
- Manufacturer: [ARISAKA DEFENSE](#)
- Product no.: 100040232
- Mfr. No.: OOM-P12
- Bullet Style: -
- Caliber: -
- Colour: Black
- Diameter (in): -
- Fits / Used For: -
- Grain: -
- Material: -
- Number of Bases: -
- Style: -
- Delivery weight: 0.041kg
- Shipping height: 25mm
- Shipping width: 51mm
- Shipping length: 102mm

- UPC: 601557939784

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #12 TALL HEIGHT (1.9"2.2") OPTIC PLATE
- About Us

Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #12 TALL HEIGHT (1.9"2.2") OPTIC PLATE

Introduction

Thank you for choosing the OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #12. This product is designed to enhance your shooting experience by providing a modular mounting solution for red dot sights. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Always inspect the product before use to ensure it is free from defects.
- Use the product only for its intended purpose as described in this guide.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe conditions or accidents to the appropriate authorities.
- Stay informed about product recalls through the EU Safety Gate platform.

Specific Safety Precautions for Use

- Ensure that the OFFSET OPTIC MOUNT is securely attached to the Picatinny rail of your AR15 rifle before use.
- Do not exceed the specified weight limit of the mount; it is designed to hold a red dot sight weighing up to 1.9 oz without optic.
- Avoid using the mount with incompatible optics that may not fit securely.
- Always ensure that the optic is centered over the bore when using the offset position.
- Do not make adjustments to the mount while the rifle is loaded or in a potentially unsafe position.

Instructions for Installation and Usage

Installation

1. **Preparation:** Gather all necessary tools, including IP20 and IP27 Torx Plus bit drivers included with the base.
2. **Attach the Base:**
 - Align the base of the OFFSET OPTIC MOUNT with the top Picatinny rail of your AR15 rifle.
 - Securely fasten the base using the twin recoil lugs and clamping screw. Ensure it is tightened to prevent movement during use.
3. **Select Optic Plate:**
 - Choose the appropriate optic plate based on your red dot sight model as indicated in the specifications.
 - Plates can be reversed for left or right side use.
4. **Attach the Optic:**
 - Place your red dot sight onto the selected optic plate.
 - Ensure the optic is secured tightly to prevent it from shifting during use.

Usage

- When canted to use the offset red dot sight, ensure that the optic remains centered over the bore.
- Maintain a lower 1/3 cowitness height for optimal sight alignment.
- Regularly check the tightness of the mount and optic to ensure safe operation.

Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic and metal waste.
- Do not dispose of the product in regular household waste.
- Consider recycling the materials when possible.

Contact Information for Further Support

For any inquiries regarding the safety of this product or to report any issues, please reach out to your local distributor or manufacturer. Ensure you have the product details handy for efficient assistance.

Thank you for your attention to these safety instructions. Your safety and satisfaction are our top priority. Enjoy your shooting experience with the OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #12!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk