

FC-G2 BIPODS - ACCU-TAC FC-4 G2 ARCA SPEC QD BIPOD

[Shooting Accessories](#) > [Bipods, Monopods & Accessories](#) > [Bipods](#)

ACCU-TAC FC-G2 BIPODS The Accu-Tac F-G2 F-Class Bipod is available with a Quick-Detach or Arca Spec Mount. They were designed, engineered, and manufactured in the USA. These bipods are perfect for long range, target, competition, and tactical shooting. The FC-G2 is 100% billet, made from the highest quality aircraft aluminum available. Accu-Tech's quick detach rail mount is simple, quick, and very secure. The quick detach attaches to a 1913 Picatinny rail and mounts in seconds without the need to use extra tools for tightening. Their F-Class has the ability to pan, and cant. The leg design allows the shooter to quickly adjust to 5 different positions with the advantage of being able to position each leg differently. To engage or adjust leg position, simply pull the leg downward to move each leg independently. Leg positions can be deployed in a 45 or 90 degree position either forwards or backwards, locking securely into 5 positions through a 180 degree arch. The quick detach rail mount is simple, quick, and very secure. The quick detach attaches to a standard Arca Swiss or Arca style rail and mounts in seconds without the need to use extra tools for tightening. Our F-Class has the ability to pan as well as cant. The leg design allows the shooter to quickly adjust to 5 different positions with the advantage of being able to position each leg differently. To engage or adjust leg position, simply pull the leg downward to move each leg independently. Leg positions can be deployed in a 45 or 90 degree position either forwards or backwards, locking securely into 5 positions through a 180 degree arch. Quick Detach: Materials 6061 T6 Aluminum Alloy Min. Height 5.25"/133.4mm (Legs at 45°) Max Height 8.25"/209.5mm (Legs at 90° deployed) Max Stance 16.50"/419mm(Legs at 90° deployed) Min Stance 12.25" 311mm (Legs at 45°) Coating Type 111 (MIL-SPEC) Hard Anodize Weight 28.2 oz Arca Spec: Materials 6061 T6 Aluminum alloy / High strength steel hardware Min. Height (Legs at 45°) 5.50" / 139.7 mm Min. Height (Legs at 90°) 7.0" / 177.8 mm Max. Height (Legs at 90°) 8.50" / 209.5 mm Min. Stance (Legs at 45°) 12.25" / 311 mm Max. Stance (Legs at 90°) 16.50" / 419 mm Closed Position Width 7.5" / 190.5 mm Closed Position Length 7.5" / 190.5 mm Weight 29.16 oz



Attributes

- Name: [ACCU-TAC FC-4 G2 ARCA SPEC QD BIPOD](#)
- Manufacturer: [ACCU-TAC](#)
- Product no.: 100040477
- Mfr. No.: FCASQD-G204
- Attachment: Quick Detach
- Colour: Black
- Feet Material: Rubber
- Folding: Yes
- Height: 5.5 to 8.5
- Style: Pivot
- Weight: 29.16 oz
- Delivery weight: 1.451kg
- Shipping height: 133mm
- Shipping width: 267mm
- Shipping length: 343mm

- UPC: 858520006299

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for ACCUTAC FCG2 Bipods
- About Us

Safety Instruction Guide for ACCUTAC FCG2 Bipods

Introduction

Thank you for choosing the ACCUTAC FCG2 Bipod. This guide provides essential safety instructions and usage guidelines to ensure your safety and the effective use of the product. Please read this document carefully before using the bipod.

General Safety Guidelines

- Ensure the bipod is used in accordance with the manufacturer's instructions to minimize risks.
- Always inspect the bipod for any signs of damage or wear before use.
- Only use the bipod on stable, level surfaces to prevent tipping or falling.
- Do not exceed the weight limit specified by the manufacturer to avoid structural failure.
- Keep the bipod away from children and unauthorized users.
- In case of any malfunction, discontinue use immediately and seek professional assistance.

Specific Safety Precautions for Use

- **Avoid Overloading:** Do not place more weight on the bipod than it is designed to support.
- **Leg Positioning:** Always ensure that the legs are securely locked in place before use to prevent accidents.
- **Adjusting Legs:** When adjusting leg positions, ensure your hands are clear of moving parts to avoid pinching.
- **Panning and Canting:** Use caution when panning and canting to maintain stability and control.
- **Weather Conditions:** Avoid using the bipod in extreme weather conditions which may affect its performance and your safety.
- **Transporting:** When transporting the bipod, ensure it is secured to prevent it from moving or causing injury.

Instructions for Installation and Usage

1. Mounting the Bipod:

- Ensure the bipod is compatible with your firearm or equipment.
- Attach the bipod to a 1913 Picatinny rail or Arca Swiss rail as per the specifications.
- Securely fasten the quick detach mount to avoid any loosening during use.

2. Adjusting the Legs:

- To adjust the leg height, pull the leg downward to unlock it. Move to the desired position and release to lock.
- The legs can be positioned at either 45 or 90 degrees. Ensure they are locked securely before use.

3. Using the Bipod:

- Position the bipod on a stable surface and ensure it is level.
- Engage the panning and canting features as needed, ensuring stability throughout the process.
- Always maintain a firm grip on the firearm while using the bipod.

4. PostUse Care:

- After use, clean the bipod with a soft cloth to remove dirt and debris.
- Store the bipod in a cool, dry place away from direct sunlight to prevent deterioration.

Disposal Instructions

- Dispose of the bipod and any associated materials in accordance with local regulations.
- Do not dispose of the bipod in regular household waste if it contains hazardous materials.
- Consider recycling options where available to minimize environmental impact.

Contact Information for Further Support

For any inquiries regarding safety or product issues, please contact the manufacturer directly. Ensure you have the product details on hand for a more efficient response.

By following these guidelines, you can ensure safe and effective use of your ACCUTAC FCG2 Bipod. Thank you for your attention to safety, and enjoy your shooting experience!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk