

BR-4 G2 BOLT ACTION BIPODS - ACCU-TAC BR-4 G2 BIPOD ARCA SPEC QD BIPOD MATTE BLACK

[Shooting Accessories](#) > [Bipods, Monopods & Accessories](#) > [Bipods](#)

ACCU-TAC BR-4 G2 BOLT ACTION BIPODS The Accu-Tac BR-4 G2 Bolt Action Bipod with the quick detach was designed, engineered, and manufactured in the USA. This smaller bipod is convenient for a more grounded shot. The BR-4 is 100% billet, made from the highest quality aircraft aluminum available.

Accu-Tac's quick detach rail mount is simple, quick, and very secure. The quick detach attaches to a 1913 Picatinny rail and mounts in seconds without the need to use extra tools for tightening. Their leg design allows the shooter to quickly adjust to 5 different positions with the advantage of being able to position each leg differently. The updated G2 model now offers leg extensions with a total of 5 notches for additional height. The BR-4 G2 has the ability to cant which can be locked with its new throw lever. To engage or adjust leg position, simply pull the leg downward to move each leg independently. Leg positions can be deployed in a 45 or 90 degree position either forwards or backwards, locking securely into 5 positions through a 180 degree arch."

Accu-Tac's quick detach rail mount is simple, quick, and very secure. The quick detach attaches to a standard Arca Swiss or Arca style rail and mounts in seconds without the need to use extra tools for tightening. Their leg design allows the shooter to quickly adjust to 5 different positions with the advantage of being able to position each leg differently. The updated G2 model now offers leg extensions with a total of 5 notches for additional height. The BR-4 G2 has the ability to cant which can be locked with its new throw lever. To engage or adjust leg position, simply pull the leg downward to move each leg independently. Leg positions can be deployed in a 45 or 90 degree position either forwards or backwards, locking securely into 5 positions through a 180 degree arch. Quick Detach: Materials 6061 T6 Aluminum alloy / High strength steel hardware Min. Height (Legs at 45°) 5.5" / 140 mm Min. Height (Legs at 90°) 6.75" / 171.5 mm Max. Height (Legs at 90°) 8.25" / 210 mm Min. Stance (Legs at 45°) 8.0" / 203 mm Max. Stance (Legs at 90°) 12.25" / 311 mm Closed Position Width 3.250" / 82.5 mm Closed Position Length 7.5" / 190 mm Weight 20 oz Color Flat Black Coating Type III (MIL-SPEC) Hard Anodize Arca Spec: Materials 6061 T6 Aluminum alloy / High strength steel hardware Min. Height (Legs at 45°) 5.75" / 146.0 mm Min. Height (Legs at 90°) 7.0" / 177.8 mm Max. Height (Legs at 90°) 8.625" / 219.0 mm Min. Stance (Legs at 45°) 8.0" / 203mm Max. Stance (Legs at 90°) 12.25" / 311 mm Closed Position Width 3.25" / 82.5 mm Closed Position Length 7.5" / 190 mm Weight 21.12 oz Color Flat Black Coating Type III (MIL-SPEC) Hard Anodize



Attributes

- Name: [ACCU-TAC BR-4 G2 BIPOD ARCA SPEC QD BIPOD MATTE BLACK](#)
- Manufacturer: [ACCU-TAC](#)
- Product no.: 100040482
- Mfr. No.: BRASQD-G204
- Attachment: Arca
- Colour: Black
- Feet Material: Rubber
- Folding: Yes
- Height: 5.75 to 8.25

- Weight: 21.2 oz
- Delivery weight: 0.907kg
- Shipping height: 83mm
- Shipping width: 140mm
- Shipping length: 324mm
- UPC: 858520006312

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for the ACCUTAC BR4 G2 Bolt Action Bipod
- About Us

Safety Instruction Guide for the ACCUTAC BR4 G2 Bolt Action Bipod

Introduction

Thank you for choosing the ACCUTAC BR4 G2 Bolt Action Bipod. This guide provides essential safety information and instructions to ensure the proper and safe use of your bipod. Please read this manual carefully before using the product.

General Safety Guidelines

- Ensure that the bipod is used only for its intended purpose as a firearm accessory.
- Regularly inspect the bipod for any signs of damage or wear before each use.
- Keep the bipod out of reach of children and unauthorized users.
- Do not modify the bipod in any way, as this may compromise safety and performance.
- Always follow local laws and regulations regarding firearm accessories and their use.
- If you experience any issues with the bipod, cease use immediately and consult a qualified professional.

Specific Safety Precautions for Use

- Always ensure that the bipod is securely attached to the firearm before use.
- Use the bipod on stable ground to prevent tipping or instability.
- When adjusting leg positions, ensure that fingers and other body parts are clear of moving parts to prevent injury.
- Be cautious when using the cant feature; ensure it is locked in place before taking a shot.
- Do not exceed the maximum weight limit specified by the manufacturer to avoid structural failure.
- Avoid using the bipod in extreme weather conditions that may affect its performance.

Instructions for Installation and Usage

Installation

1. **Select the Rail:** Choose either a 1913 Picatinny rail or an Arca Swiss/Arca style rail for mounting.
2. **Attach the Bipod:** Align the bipod's quick detach mount with the rail and slide it into place. Ensure it is securely locked.
3. **Check Stability:** After attaching, gently pull on the bipod to ensure it is firmly in place.

Usage

1. **Adjusting Leg Positions:**
 - Pull the leg downward to adjust its position.
 - The legs can be deployed in a 45 or 90degree position, either forwards or backwards.
 - Ensure that each leg is locked securely into one of the five available positions.
2. **Using the Cant Feature:**
 - To engage the cant, loosen the throw lever.
 - Adjust the cant to the desired angle and tighten the lever to lock it in place.
3. **Height Adjustments:**
 - The updated G2 model allows for leg extensions with five notches for additional height.
 - Adjust the legs to achieve the desired height based on your shooting position.

Disposal Instructions

- Dispose of the bipod in accordance with local regulations regarding electronic and metal waste.

- If the product is damaged beyond repair, ensure that it is rendered unusable before disposal.
- Recycle materials where possible to minimize environmental impact.

Contact Information for Further Support

For any safety inquiries or concerns regarding the ACCUTAC BR4 G2 Bolt Action Bipod, please refer to the manufacturer's official website or contact their customer service department for assistance.

Thank you for prioritizing safety while using the ACCUTAC BR4 G2 Bolt Action Bipod. Enjoy your shooting experience responsibly!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk