

AR-15 XTREME TRIGGERS 2-STAGE - HIPERFIRE XTREME MOD-3 TRIGGER 2-STAGE FLAT

[Rifle Parts](#) > [Triggers Parts](#) > [Triggers](#)

AR-15 XTREME TRIGGERS 2-STAGE Whether you shoot competitively, train to defend yourself and your family, or you simply want to enjoy shooting out on the range, ensuring your rifle goes "bang" every time, without fail, is important. The HIPERFIRE Xtreme two-stage triggers feature the same technology that HIPERFIRE has become known for. Higher hammer strike energy, soft start lock-up technology, user adjustable pull weights, mil-grade components, and precision manufacturing come together to make one of the most robust two-stage triggers available today. Available in 2 different models. Mod-2 2 Stage Curved: Minimal, user adjustable, 2 - 3 pound first stage Minimal second stage wall with a 1 ½ pound weight Total 3 ½ - 4 ½ pound pull with green or red toggle springs respectively Shorter first stage than Mod-1 for a more fine-tuned feel Curved trigger bow allows for the addition of the HIPERSHOE® (sold separately) Mod-3 2-Stage Flat: Minimal, user adjustable, 2 - 3 pound first stage Minimal second stage wall with a 1 ½ pound weight Total pull 3 ½ - 4 ½ pound with green or red toggle springs respectively Shorter first stage than Mod-1 for a more fine-tuned feel Flat trigger bow includes HIPERSHOE® Both models include the following features: Distinct wall between first and second stages allows for effective "prepping" of the trigger for added confidence Clean, effortless break Weightless, imperceptible over-travel Include adjustment springs HIPERFIRE Xtreme triggers are compatible with AR-15s, 308 style ARs, and 9mm or PPC style ARs including the Six MPX.



Attributes

- Name: [HIPERFIRE XTREME MOD-3 TRIGGER 2-STAGE FLAT](#)
- Manufacturer: [HIPERFIRE](#)
- Product no.: 100041030
- Mfr. No.: X2SM3
- Style: 2-Stage
- Delivery weight: 0.132kg
- Shipping height: 25mm
- Shipping width: 108mm
- Shipping length: 171mm
- UPC: 859177004508

Item details

Made in USA

US export classification: 0A501.c

Table of Contents

- Startpage
- Safety Instruction Guide for AR15 XTREME TRIGGERS 2STAGE HIPERFIRE XTREME MOD3 TRIGGER 2STAGE FLAT
- About Us

Safety Instruction Guide for AR15 XTREME TRIGGERS 2STAGE HIPERFIRE XTREME MOD3 TRIGGER 2STAGE FLAT

Introduction

Thank you for choosing the AR15 XTREME TRIGGERS 2STAGE HIPERFIRE XTREME MOD3 TRIGGER 2STAGE FLAT. This guide provides essential safety instructions to ensure the safe and effective use of your trigger. It is important to read and understand these instructions before handling or using the product.

General Safety Guidelines

- Ensure that all firearms are handled with care and respect at all times.
- Always treat every firearm as if it is loaded.
- Keep the firearm pointed in a safe direction.
- Store firearms and ammunition safely, away from children and unauthorized users.
- Regularly inspect your trigger and firearm for any signs of wear or damage.
- Report any unsafe products or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure that the trigger is compatible with your firearm model (AR15s, 308 style ARs, and 9mm or PPC style ARs).
- Do not modify the trigger or firearm in any way that could affect safety or performance.
- Use only the recommended adjustment springs provided with the product.
- Be mindful of the trigger pull weight settings, especially when adjusting for personal preference.
- Avoid using the trigger while under the influence of alcohol or drugs.

Instructions for Installation and Usage

Installation

1. Preparation

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather necessary tools for installation.

2. Remove the Existing Trigger

- Follow the manufacturer's instructions for disassembling your firearm to access the trigger assembly.
- Carefully remove the existing trigger from the firearm.

3. Install the HIPERFIRE XTREME Trigger

- Align the new trigger with the trigger housing.
- Secure the trigger in place according to the manufacturer's instructions.
- Ensure that all components are properly seated and tightened.

4. Adjust the Trigger Settings

- Set the first stage pull weight to your desired level (2 3 pounds).
- Adjust the second stage wall to a minimal weight (1 ½ pounds).

- Test the trigger to ensure it operates smoothly.

5. Reassemble the Firearm

- Once the trigger is installed and adjusted, reassemble the firearm according to the manufacturer's instructions.
- Perform a safety check to ensure proper function.

Usage

- Before each use, conduct a thorough safety inspection of your firearm and trigger.
- Practice safe handling techniques at all times.
- Familiarize yourself with the trigger's characteristics, including the distinct wall between the first and second stages.
- Regularly practice using the trigger to build confidence and proficiency.

Disposal Instructions

- When disposing of the trigger or any firearm components, follow local regulations for hazardous waste disposal.
- Ensure that the trigger is rendered inoperable before disposal.
- Recycle materials when possible, following local guidelines.

Contact Information for Further Support

For any inquiries or support regarding the AR15 XTREME TRIGGERS 2STAGE HIPERFIRE XTREME MOD3 TRIGGER 2STAGE FLAT, please refer to the manufacturer's website or contact their customer service.

By following these guidelines, you can ensure a safe and enjoyable experience with your AR15 XTREME TRIGGERS 2STAGE HIPERFIRE XTREME MOD3 TRIGGER 2STAGE FLAT. Stay safe and responsible while enjoying your shooting activities.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk