

AR .308 COMBAT RAIL HANDGUARDS M-LOK - MIDWEST INDUSTRIES AR 308 15" COMBAT RAIL HANDGUARD DPMS HIGH M-LOK BLACK

[Rifle Parts](#) > [Build Kits](#) > [Handguards & Rails](#)

A Dedicated DPMS-Compatible AR .308 Handguard

Looking to take your DPMS-pattern AR .308 rifle to the next level? This enhanced Combat Rail M-LOK Handguard from Midwest Industries is purpose-built to provide added versatility and durability to your rifle, and it looks great, to boot! Each Midwest Industries AR .308 Combat Rail Handguard is machined from 6061 aluminum and treated with a hardcoat-anodized black finish. The handguard comes with a torque plate made from 4140 steel, along with an aluminum anti-rotation block. The handguard features five separate anti-rotation quick-detach sling socket points, as well as three sides of M-LOK-compatible rail slots. A single five-slot rail is included with the handguard. Designed for use on DPMS High or Low receivers, the Midwest Industries AR .308 Combat Rail Handguard will fit on receivers with a .210-inch tang height. The free-float design is available in 12.625- and 15-inch lengths and features a width of 1.75 inches and a height of 2.187 inches. The unit attaches with a heat-treated, 4140-steel barrel nut with 1 7/16-16 TPI threads. A barrel nut wrench is included for installation.



Attributes

- Name: [MIDWEST INDUSTRIES AR 308 15" COMBAT RAIL HANDGUARD DPMS HIGH M-LOK BLACK](#)
- Manufacturer: [MIDWEST INDUSTRIES](#)
- Product no.: 100041116
- Mfr. No.: MI-CR308-15
- Colour: Black
- Length: 15
- Material: Aluminum
- Style: M-LOK
- Type: Free Float
- Weapon type: AR .308
- Delivery weight: 0.59kg
- Shipping height: 102mm
- Shipping width: 102mm
- Shipping length: 432mm
- UPC: 812102033196

Item details

Made in USA
US export classification: 0A501.y.1

Table of Contents

- Startpage
- Safety Instruction Guide for AR .308 Combat Rail Handguards MLOK
- About Us

Safety Instruction Guide for AR .308 Combat Rail Handguards MLOK

Introduction

Thank you for choosing the AR .308 Combat Rail Handguard MLOK from Midwest Industries. This product is designed to enhance the functionality and durability of your DPMSpattern AR .308 rifle. To ensure safe and effective use, please read this safety instruction guide carefully.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose as described in the product specifications.
- Always follow local laws and regulations regarding firearm accessories and modifications.
- Inspect the handguard and its components before each use to ensure they are in good condition.
- Keep the product out of reach of children and unauthorized users.
- Report any unsafe conditions or accidents to the relevant authorities immediately.
- Stay informed about product recalls by checking the EU's Safety Gate platform regularly.

Specific Safety Precautions for Use

- **Potential Hazards:** Improper installation or use can lead to firearm malfunction or injury.
- **Avoiding Hazards:**
 - Ensure the firearm is unloaded before installation.
 - Use only the provided barrel nut wrench to secure the handguard.
 - Do not exceed the recommended torque specifications during installation.
 - Regularly check the handguard for signs of wear or damage.
 - Do not modify or alter the handguard in any way.
- **Age Specific Warnings:** This product is not intended for use by individuals under the age of 18. Ensure that any handling or installation is supervised by a responsible adult.

Instructions for Installation and Usage

1. Preparation:

- Ensure your work area is clean and free of distractions.
- Gather necessary tools: barrel nut wrench (included) and any additional tools required for your specific firearm.

2. Installation Steps:

- **Unload the Firearm:** Ensure the firearm is completely unloaded and pointed in a safe direction.
- **Remove Existing Handguard:** If applicable, carefully remove the existing handguard from your rifle.
- **Attach the Barrel Nut:**
 - Install the heat treated 4140 steel barrel nut onto the receiver.
 - Use the barrel nut wrench to tighten it securely, following the manufacturer's torque specifications.
- **Install the Handguard:**
 - Slide the handguard onto the barrel nut.
 - Ensure that the antirotation block is properly positioned.
 - Secure the handguard using the provided torque plate and screws.

- **Check Stability:** Once installed, check that the handguard is securely attached and does not move.

3. Usage:

- The handguard features five antirotation quickdetach sling socket points. Use these for attaching slings as needed.
- Utilize the MLOKcompatible rail slots for mounting accessories as desired.

4. PostInstallation Check:

- After installation, perform a thorough check to ensure that all components are secure and functioning correctly.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic and metal waste.
- Do not dispose of the product in regular household waste.
- If the product is damaged or no longer usable, consider recycling components where possible.

Contact Information for Further Support

- For any questions regarding the installation, usage, or safety of the AR .308 Combat Rail Handguard, please refer to the manufacturer's website or contact their customer support directly.

Thank you for your attention to these safety instructions. Proper use and adherence to these guidelines will help ensure a safe and enjoyable experience with your AR .308 Combat Rail Handguard MLOK.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk