

RESCUE FRONT SIGHT BLANK - HARRISON DESIGN & CONSULTING

RESCUE FRONT SIGHT BLANK, .375 X 65 X .085

[Handgun Parts](#) > [Sights](#) > [Front Sights](#)

Ted Yost developed and made these sights several years ago and after a long absence from the marketplace they are once again available from Harrison Design. These sights can be used to rescue a slide from mis-cut front dovetails. They have an oversize dovetail base featuring nominal dimensions of .085"" depth, .375"" width with a 65 dovetail angle. That's big enough to rescue most any sort of ugliness and butchery. The blade is .275"" tall X .630"" long X .125 wide. The vertical rill pin has been omitted so you can match it's location to wherever your slide's hole location is located. The dovetail base is .625"" wide, so it can be blended to the top of your slide, or you can cut the sides back for the appearance you want. A radius is machined at the point where the blade joins the dovetail base, strengthening the sight appreciably. This is a part that every gunsmith should keep 2 or 3 of on hand as it can get you out of a jam is a slip up is made. It can be cut down and made into other sight blanks as well. It's a great tool for your toolbox you use to be a great gunsmith!



Attributes

- Name: [HARRISON DESIGN & CONSULTING RESCUE FRONT SIGHT BLANK, .375 X 65 X .085](#)
- Manufacturer: [HARRISON DESIGN & CONSULTING](#)
- Product no.: 100045341
- Mfr. No.: HD-013
- Height: .275
- Outline: None
- Style: Blank
- Weapon type: 1911
- Width: .125
- Delivery weight: 0.009kg
- Shipping height: 13mm
- Shipping width: 76mm
- Shipping length: 152mm

Item details

Made in USA

Table of Contents

- Startpage
- RESCUE FRONT SIGHT BLANK Safety Instruction Guide
- About Us

RESCUE FRONT SIGHT BLANK Safety Instruction Guide

Introduction

Thank you for choosing the RESCUE FRONT SIGHT BLANK by Harrison Design & Consulting. This product is designed to assist gunsmiths in correcting miscut front dovetails on slides. To ensure safe and effective use of this product, please read and follow the safety instructions and guidelines outlined in this document.

General Safety Guidelines

- Ensure that you are familiar with the safe handling of firearms and related components.
- Always wear appropriate protective equipment, including safety glasses and gloves, when working with tools and firearm components.
- Keep the work area clean and organized to prevent accidents.
- Always work in a wellventilated area, especially when using tools that may produce dust or debris.
- Be aware of your surroundings and ensure that unauthorized individuals, especially children, are kept at a safe distance while you are working.

Specific Safety Precautions for Use

- Do not use the RESCUE FRONT SIGHT BLANK if it appears damaged or defective.
- Ensure that the dovetail base is properly aligned before installation to avoid unnecessary force or damage.
- Be cautious when cutting or modifying the sight blank; improper handling may result in injury.
- Always doublecheck the compatibility of the sight blank with your specific firearm model before installation.
- If you are unsure about any aspect of using this product, consult a qualified gunsmith for assistance.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary tools, including a dovetail cutter, files, and measuring tools.
- Ensure your work area is clean and welllit.

2. Measuring and Marking

- Measure the existing dovetail on your slide to determine the correct position for the RESCUE FRONT SIGHT BLANK.
- Mark the alignment points clearly.

3. Cutting the Dovetail

- Using a dovetail cutter, carefully cut the new dovetail according to the marked measurements.
- Take your time to ensure a precise fit.

4. Fitting the Sight Blank

- Insert the RESCUE FRONT SIGHT BLANK into the newly cut dovetail.
- Ensure that the sight is flush with the top of the slide.
- If necessary, use files to adjust the fit.

5. Securing the Sight Blank

- Once properly fitted, secure the sight blank in place.
- Follow any additional manufacturer instructions for securing the sight if applicable.

6. Final Checks

- Inspect the installation to ensure it is secure and correctly aligned.
- Test the sight for stability before using the firearm.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the RESCUE FRONT SIGHT BLANK becomes damaged beyond repair, dispose of it as per local electronic waste disposal guidelines to minimize environmental impact.

Contact Information for Further Support

For any safety inquiries or concerns regarding the RESCUE FRONT SIGHT BLANK, please refer to the contact information provided by the manufacturer or authorized distributor. Always ensure that you have access to support for any questions or issues you may encounter during installation or use.

Conclusion

By following these safety instructions and guidelines, you can ensure a safe and efficient experience while using the RESCUE FRONT SIGHT BLANK. Always prioritize safety and consult professionals when in doubt. Thank you for your attention to these important safety measures.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk