

COATED STEEL CLEANING RODS - OUTERS COATED STEEL CLEANING ROD 1-PIECE UNIVERSAL 33

[Gun Cleaning & Chemicals](#) > [Cleaning Rods & Accessories](#) > [Cleaning Rods](#)

Highlights: One-piece design requires no assembly before use Full-size rod covers full length of bore No annoying loose sections while in use Constructed using strong, long-lasting coated steel Includes attachment tips such as nylon jags, nylon loops, and/or a rod adaptor



Attributes

- Name: [OUTERS COATED STEEL CLEANING ROD 1-PIECE UNIVERSAL 33](#)
- Manufacturer: [OUTERS](#)
- Product no.: 100046101
- Mfr. No.: 41642
- Caliber: Universal
- Material: Steel
- Style: Rifle
- Delivery weight: 0.168kg
- Shipping height: 25mm
- Shipping width: 70mm
- Shipping length: 902mm
- UPC: 076683416421

Table of Contents

- [Startpage](#)
- [COATED STEEL CLEANING RODS SAFETY INSTRUCTIONS](#)
- [About Us](#)

COATED STEEL CLEANING RODS SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the Outers Coated Steel Cleaning Rod. This guide provides essential safety instructions to ensure the safe and effective use of this product. Please read this document carefully before use.

General Safety Guidelines

- Ensure that the cleaning rod is used only for its intended purpose.
- Always inspect the cleaning rod before use for any signs of damage or wear.
- Keep the cleaning rod out of reach of children and vulnerable individuals.
- Use appropriate personal protective equipment (PPE) such as gloves and safety glasses when cleaning firearms.
- Follow all local laws and regulations regarding the cleaning and maintenance of firearms.

Specific Safety Precautions for Use

- Do not use the cleaning rod if it is damaged or if any attachment tips are missing.
- Always follow the manufacturer's instructions for using the cleaning rod and its attachments.
- Avoid using excessive force when cleaning to prevent damage to the firearm or cleaning rod.
- Ensure that the firearm is unloaded and pointed in a safe direction before use.
- Use the cleaning rod in a wellventilated area to avoid inhaling any cleaning solvents.

Instructions for Installation and Usage

1. Prepare the Cleaning Rod:

- Remove the cleaning rod from its packaging.
- Inspect the rod for any visible damage or defects.

2. Attach the Desired Tip:

- Choose the appropriate attachment tip (nylon jag, nylon loop, or rod adaptor).
- Securely attach the tip to the end of the cleaning rod.

3. Prepare the Firearm:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Open the action of the firearm to access the bore.

4. Insert the Cleaning Rod:

- Carefully insert the cleaning rod into the bore.
- Use a gentle twisting motion to guide the rod through the bore.

5. Clean the Bore:

- Apply the appropriate cleaning solvent to the attachment tip.
- Pull the cleaning rod through the bore in a smooth motion.
- Repeat as necessary, ensuring that you do not force the rod.

6. Remove and Clean the Rod:

- After cleaning, carefully remove the cleaning rod from the bore.
- Clean the attachment tips as needed and store the cleaning rod in a safe place.

Disposal Instructions

- Dispose of any cleaning solvents and materials according to local regulations.
- If the cleaning rod is damaged beyond repair, dispose of it in accordance with local waste management guidelines.

Contact Information for Further Support

For any questions or concerns regarding the safety and usage of the Outers Coated Steel Cleaning Rod, please contact the manufacturer directly through the designated customer support channels.

Conclusion

By following these safety instructions, you can ensure a safe and effective cleaning experience with your Outers Coated Steel Cleaning Rod. Remember to prioritize safety and compliance with local laws while maintaining your firearms. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk