

RS REPLACEMENT PLUNGERS - RIFLESPEED PLUNGER 927

[Rifle Parts](#) > [Gas System Parts](#) > [Gas Pistons](#)

If you like to keep spare parts on hand for maintenance or replacement, add the appropriate size Plunger to your kit. Plunger service life varies from 10,000 to 25,000 rounds, depending on your firing schedule. When you replace a worn-out barrel or bolt or when the working end of your Plunger has been worn away by half, then it's time for a new plunger. You can also select shorter or longer plungers to fine tune the range of adjustments used for your specific firearm. This provides a tremendous amount of flexibility thanks to the modular design of the RIFLESPEED™ line of Gas Controls. For example; you've completed the setup instructions found on [riflespeed.com](#) and determined that with Plunger 937 installed your carbine uses setting number 1-6 for suppressed fire with milspec ammo and setting number 1-11 for unsuppressed fire with commercial 223 .amm. You determined these settings on your local range during the early summer when temperatures were in the mid 80s. Since more gas will be required during extreme cold winter temperatures you can select a shorter plunger like Plunger 917 to shift the position of your ideal settings to the lower portion of the adjustment range. Since every plunger number represents a shift of 2 positions on your control knob, instead of using settings number 1-6 and 1-11 you'll now be using settings number 1-2 and 1-7 for suppressed and unsuppressed fire, respectively. So what's the purpose of doing this? Shifting the range of adjustments to lower numbers allows you to have more room to increase gas later when temperatures drop without having to dial past the Rotation Stop to use Rotation Range Two. Since cold guns need more pressure to run and cold ammo produces less pressure, it's important to be able to increase gas flow when temperatures plummet. Selecting the specific plunger that puts your preferred settings in the lower third of the adjustment range gives you the most potential adjustment range. The opposite holds true if you've determined your firearm's settings during cold conditions. You may want to select a longer plunger to insure that you can reduce gas when summer heat arrives. Again, this process is not a necessary step as the plunger provided with your Gas Control has been selected for general-purpose use in most configurations, but the ability to easily fine tune the system is one of many benefits of the modular design of RIFLESPEED™ Gas Controls. Plunger 937 comes installed in every RIFLESPEED™ Gas Control. This is the general-purpose size that covers a broad range of firearms. Plunger 937 measures 0.937"" long and is suitable for most configurations. Plunger 917 measures 0.917"" and provides less restriction for configurations where more gas is needed to ensure reliable function. Plunger 917 also allows the use of the lower-numbered settings on your Gas Control, giving you maximum adjustment range in cold conditions where more gas is needed. Plungers 917 and 937 are included in the retail package with each RIFLESPEED™ Gas Control. These sizes provide coverage of the full range of potential settings needed for nearly every configuration we've identified during development of the RIFLESPEED™ Gas Control and allow the shooter to select the best Plunger for a specific firearm. Additional sizes are available for those who choose to precisely tune their Gas Control's settings. Keep your RIFLESPEED™ Gas Control functioning like new with genuine RIFLESPEED™ replacement parts. Made in the USA.



Attributes

- Name: [RIFLESPEED PLUNGER 927](#)
- Manufacturer: [RIFLESPEED](#)
- Product no.: 100050267
- Mfr. No.: US0110
- Delivery weight: 0.005kg
- Shipping height: 6mm
- Shipping width: 102mm
- Shipping length: 152mm

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- Startpage
- RS Replacement Plungers Riflespeed Plunger 927 Safety Instruction Guide
- About Us

RS Replacement Plungers Riflespeed Plunger 927 Safety Instruction Guide

Introduction

Thank you for choosing the RS Replacement Plungers Riflespeed Plunger 927. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read this guide carefully and keep it for future reference.

General Safety Guidelines

- **Product Safety:** Ensure that the RS Replacement Plungers are used only for their intended purpose. Follow all instructions and safety guidelines to minimize risks.
- **Enhanced Recalls:** Be aware of any recall notices related to this product. If you receive a recall notice, follow the instructions provided for returning or exchanging the product.
- **Online Shopping:** When purchasing online, ensure that the seller complies with safety requirements. Verify the product's authenticity and safety certifications.
- **Special Consumer Focus:** This product is not intended for use by children. Keep it out of reach of minors to prevent accidents.
- **EU Contact Point:** For any safety inquiries about this product, refer to the contact information provided by the retailer or manufacturer.
- **Rapid Alerts:** Stay informed about any updates regarding product safety through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Inspection:** Before using the plunger, inspect it for any signs of wear or damage. Do not use if damaged.
- **Installation:** Follow the installation instructions carefully. Improper installation may lead to malfunction or injury.
- **Usage:** Use the plunger only with compatible firearms as specified in the product documentation.
- **Environment:** Avoid using the product in extreme temperatures or conditions that may affect its performance.
- **Maintenance:** Regularly check and maintain your plunger to ensure optimal performance and safety.
- **Handling:** Handle the plunger with care. Avoid dropping or mishandling it to prevent damage.

Instructions for Installation and Usage

1. Installation:

- Ensure your firearm is unloaded and safe before starting the installation.
- Remove the existing plunger from the Gas Control according to the manufacturer's instructions.
- Select the appropriate RS Replacement Plunger based on your firearm's configuration and needs.
- Insert the new plunger into the Gas Control, ensuring it is seated properly.
- Doublecheck that the installation is secure before proceeding.

2. Usage:

- Familiarize yourself with the adjustment settings of your Gas Control.
- Regularly monitor the performance of your firearm and adjust the plunger settings as needed for optimal operation.
- If you notice any irregularities in performance, discontinue use and consult a qualified gunsmith.

Disposal Instructions

- Dispose of any old or damaged plungers in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Check with local authorities for specific disposal guidelines for firearm accessories.

Contact Information for Further Support

For any questions or concerns regarding the RS Replacement Plungers Riflespeed Plunger 927, please refer to the contact information provided by your retailer or manufacturer.

Thank you for your attention to these safety guidelines. Your safety is our priority.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk