

HIGH PRESSURE CASE SIZING LUBRICANT - FORSTER HIGH PRESSURE CASE SIZING LUBRICANT 2 OZ.

[Reloading](#) > [Case Preparation](#) > [Case Lube](#)

It requires tremendous force to drive an unlubricated case into a full length resizing or forming die. But, the wrong lubricant can ruin cases or break shell holders. Forsters high pressure lubricant adheres to the case when it's forced into the die and you can barely feel the cases enter and exit the die. This high quality lubricant makes resizing easy and it saves your equipment. Available in 2 oz. plastic bottles. (Oil based lubricant)



Attributes

- Name: [FORSTER HIGH PRESSURE CASE SIZING LUBRICANT 2 OZ.](#)
- Manufacturer: [FORSTER](#)
- Product no.: 100203482
- Mfr. No.: 011071
- Delivery weight: 0.136kg
- Shipping height: 12mm
- Shipping width: 95mm
- Shipping length: 128mm
- UPC: 757253001857

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for Forster High Pressure Case Sizing Lubricant](#)
- [About Us](#)

Safety Instruction Guide for Forster High Pressure Case Sizing Lubricant

Introduction

Thank you for choosing Forster High Pressure Case Sizing Lubricant. This guide provides essential safety instructions to ensure the safe use of this product. Please read and follow these guidelines carefully to protect yourself and others.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose as a case sizing lubricant.
- Keep the lubricant out of reach of children and pets.
- Always store the product in a cool, dry place away from direct sunlight.
- Do not use the lubricant if the seal is broken or the product appears damaged.
- Be aware of any allergic reactions. If you experience irritation, discontinue use immediately and seek medical advice.
- Report any unsafe products or accidents to local authorities.

Specific Safety Precautions for Use

- Always wear protective gloves and eyewear when handling the lubricant to prevent skin and eye contact.
- Avoid ingesting the product. If ingested, seek medical attention immediately.
- Use only in wellventilated areas to avoid inhaling vapors.
- Do not mix with other lubricants or chemicals.
- Dispose of any excess lubricant properly according to local regulations.

Instructions for Installation and Usage

1. Preparation:

- Ensure that your workspace is clean and welllit.
- Gather all necessary tools and equipment for resizing cases.

2. Application:

- Shake the bottle gently before use to ensure an even consistency.
- Apply a thin, even coat of lubricant to the case. Ensure full coverage to prevent sticking during resizing.
- Do not overlubricate, as this may lead to contamination or damage.

3. Resizing Process:

- Insert the lubricated case into the resizing die carefully.
- Operate the resizing equipment according to the manufacturer's instructions.
- Monitor the process to ensure smooth entry and exit of the cases.

4. PostUse:

- Clean any excess lubricant from tools and equipment immediately after use.
- Store the lubricant bottle securely with the cap tightly closed.

Disposal Instructions

- Dispose of the product and any empty containers in accordance with local waste disposal regulations.
- Do not pour lubricant down drains or into the environment.

Contact Information for Further Support

For any safety inquiries or to report issues related to the product, please contact the designated EUbased contact point provided with your product packaging or documentation.

By following these guidelines, you can ensure a safe and effective experience using Forster High Pressure Case Sizing Lubricant. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk