

PROHOLD BALL-HEX "L" WRENCH - BONDHUS PROHOLD BALL HEX L-WRENCH .050"

[Gunsmith Tools](#) > [General Gunsmith Tools](#) > [Wrenches](#) > [General Wrenches](#)

Holds Screw Snug To Wrench, Work At Angles Up To 251

BROWNELLS PROHOLD BALL-HEX "L" WRENCH A nylon button in the ball end holds screw snugly on the wrench, helps prevent dropped and lost screws. Because they can be "off" as much as 25°, ball-end, hex wrenches will work in places conventional ones won't. Use "square" end when more leverage is needed. Supplied in deluxe case with a locking slot for each wrench. SPECS: High torque steel. 2-7/8" (7.3cm) - 6" (16.5cm) long.



Attributes

- Name: [BONDHUS PROHOLD BALL HEX L-WRENCH .050"](#)
- Manufacturer: [BONDHUS](#)
- Product no.: 123000003
- Mfr. No.: 75702
- Style: Allen Wrenches
- Delivery weight: 0.005kg
- Shipping height: 1mm
- Shipping width: 25mm
- Shipping length: 89mm
- UPC: 037231757021

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [PROHOLD BALLHEX "L" WRENCH BONDHUS .050" Safety Instruction Guide](#)
- [About Us](#)

PROHOLD BALLHEX "L" WRENCH BONDHUS .050"

Safety Instruction Guide

Introduction

Thank you for choosing the PROHOLD BALLHEX "L" WRENCH by BONDHUS. This product is designed to provide you with reliable performance and ease of use. To ensure your safety and the safe operation of this tool, please read and follow the guidelines outlined in this safety instruction guide.

General Safety Guidelines

- Always use the wrench in accordance with the manufacturer's recommendations.
- Inspect the wrench before each use for any signs of damage or wear.
- Do not use the wrench for purposes other than those intended.
- Keep the wrench out of reach of children and vulnerable individuals.
- Store the wrench in a secure place when not in use, preferably in the supplied deluxe case.

Specific Safety Precautions for Use

- **Hazard Identification:**

- Potential for injury if the wrench slips during use.
- Risk of dropping screws if not properly secured in the ball end.
- Risk of overtorquing, which can damage the screw or wrench.

- **Avoiding Hazards:**

- Ensure that the screw is properly seated in the ball end before applying torque.
- Use the square end of the wrench when more leverage is needed to prevent slipping.
- Do not exceed the torque specifications of the screws you are working with.

- **AgeSpecific Warnings:**

- This product is not intended for use by children. Adult supervision is required if used by individuals under the age of 18.

Instructions for Installation and Usage

- **Installation:**

- No special installation is required for the PROHOLD BALLHEX "L" WRENCH. Simply remove the wrench from the deluxe case and ensure it is clean and free of debris before use.

- **Usage:**

- To use the wrench, select the appropriate size for the screw you are working with.
- Insert the ball end of the wrench into the screw head, ensuring it is properly seated.
- For added grip, the nylon button in the ball end will hold the screw snugly.
- Apply torque slowly and steadily. If more leverage is needed, switch to the square end of the wrench.
- After use, clean the wrench and store it in the deluxe case.

Disposal Instructions

- Dispose of the wrench responsibly at the end of its life.
- Check local regulations for proper disposal methods of metal tools.
- If the wrench is damaged or no longer usable, recycle the metal components where possible.

Contact Information for Further Support

For any questions or concerns regarding the PROHOLD BALLHEX "L" WRENCH by BONDHUS, please refer to the contact information provided on the product packaging or visit the manufacturer's website for further assistance.

By adhering to these safety guidelines, you can ensure a safe and effective experience with your PROHOLD BALLHEX "L" WRENCH. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk