

MOSSBERG POST '97 500, 590, 835, 930, 935 HD SCOPE BASES - EGW MOSSBERG 500, 590, 835, 930, 935 POST-1997

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Shotgun Bases](#)

EGW Mossberg 500, 590, 835, 930, 935 Post-1997 Heavy Duty Scope Bases. Add the versatility of a one-piece Picatinny scope rail to your shotgun with no drilling or tapping. Precision machined from extruded aluminum with Picatinny slot-and-rail spacing that allows fast and simple changes to eye relief, plus great flexibility in scope choice. Drilled to fit the factory scope mount holes on the gun's receiver. Accepts Picatinny or Weaver scope rings. Heavy Duty mounts are .100" lower than the Lightweight mounts to minimize weight and keep your optic closer to the barrel centerline for improved accuracy. Full-width cross-slots are gauged to MIL-STD 1913 specs to +/- .002". Machined from ultra-rigid extruded 7075 T6 aluminum. Includes socket head Torx® screws and wrench. EGW recommends 20 inch lbs of torque and a drip of blue loctite.



EGW Mossberg 500, 590, 835, Post-1997 Heavy Duty Scope Bases. Add the versatility of a one-piece Picatinny scope rail to your shotgun with no drilling or tapping. Precision machined from extruded aluminum with Picatinny slot-and-rail spacing that allows fast and simple changes to eye relief, plus great flexibility in scope choice. Drilled to fit the factory scope mount holes on the gun's receiver. Accepts Picatinny or Weaver scope rings. Heavy Duty mounts are .100" lower than the Lightweight mounts to minimize weight and keep your optic closer to the barrel centerline for improved accuracy. Full-width cross-slots are gauged to MIL-STD 1913 specs to +/- .002". Machined from ultra-rigid extruded 7075 T6 aluminum. Includes socket head Torx screws and wrench. EGW recommends 20 inch lbs of torque and a drip of blue loctite.

Attributes

- Name: [EGW MOSSBERG 500, 590, 835, 930, 935 POST-1997](#)
- Manufacturer: [EGW](#)
- Product no.: 296000155
- Mfr. No.: 80800
- Colour: Black
- Material: Aluminum
- Model: 500,590,835
- Number of Bases: 1-Piece
- Style: Heavy Duty Bases
- Weapon type: Mossberg
- Delivery weight: 0.068kg
- Shipping height: 25mm
- Shipping width: 81mm
- Shipping length: 208mm
- UPC: 841370109234

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for MOSSBERG POST '97 500, 590, 835, 930, 935 HD SCOPE BASES
- About Us

Safety Instruction Guide for MOSSBERG POST '97 500, 590, 835, 930, 935 HD SCOPE BASES

Introduction

Thank you for choosing the EGW Mossberg 500, 590, 835, 930, 935 Post1997 Heavy Duty Scope Bases. This guide provides essential safety instructions and guidelines to ensure safe and effective use of your product in compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Always read and understand all safety instructions before using the product.
- Ensure that the product is suitable for your specific shotgun model.
- Inspect the scope bases for any signs of damage before installation.
- Use only compatible scope rings with the Picatinny rail system.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe conditions or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Ensure the shotgun is unloaded before installation of the scope bases.
- Do not exceed the recommended torque specifications of 20 inch lbs when securing the scope bases.
- Use blue Loctite on screws to prevent loosening due to recoil.
- Regularly check the tightness of the screws and the condition of the scope bases after use.
- Never attempt to modify or alter the scope bases as this may compromise safety and performance.
- Be aware of the potential for recoil and ensure a proper grip on the shotgun when in use.

Instructions for Installation and Usage

1. Preparation:

- Ensure the shotgun is unloaded.
- Gather all necessary tools, including a Torx® wrench.

2. Installation:

- Locate the factory scope mount holes on the shotgun's receiver.
- Align the scope base over the mount holes.
- Insert the provided socket head Torx® screws into the mount holes.
- Tighten the screws to the recommended torque of 20 inch lbs using the Torx® wrench.
- Apply a small amount of blue Loctite to each screw before tightening.

3. Scope Attachment:

- Attach your Picatinny or Weaver scope rings to the installed scope base.
- Ensure the scope is securely mounted and aligned properly.

4. Usage:

- Always check that the scope is securely attached before each use.
- Maintain proper shooting posture and grip, keeping in mind the recoil of the shotgun.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste.
- Consider recycling options for aluminum components where available.

Contact Information for Further Support

For safety inquiries or further support regarding the EGW Mossberg 500, 590, 835, 930, 935 Post1997 Heavy Duty Scope Bases, please refer to the manufacturer's contact information provided with your product.

By following these guidelines, you can ensure a safe and enjoyable experience with your EGW Mossberg scope bases. Thank you for prioritizing safety and compliance.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk