

1911 LONG NOSE RECOIL SPRING PLUG - EGW LONG NOSE PLUG SOLID END BLUE

[Handgun Parts](#) > [Recoil Parts](#) > [Recoil Spring Plugs](#)

Improves The Appearance Of Pistols With Thick Bushings

Machined steel plug has an extended nose designed to fit flush with thicker-than-normal bushings for improved cosmetic appearance. Designed for use with EGW Thick Flange, Melt, or Carry Bevel bushings. Available in stainless or blued steel, with Solid End for G.I. spring guides or Open End for full-length guide rods. Fits any Government or Commander model pistol.



Attributes

- Name: [EGW LONG NOSE PLUG SOLID END BLUE](#)
- Manufacturer: [EGW](#)
- Product no.: 296000195
- Mfr. No.: 13102
- Model: Government
- Weapon type: 1911
- Delivery weight: 0.011kg
- Shipping width: 83mm
- Shipping length: 146mm
- UPC: 841370102822

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 1911 Long Nose Recoil Spring Plug](#)
- [About Us](#)

Safety Instruction Guide for 1911 Long Nose Recoil Spring Plug

Introduction

Thank you for choosing the 1911 Long Nose Recoil Spring Plug by EGW. This guide provides important safety information and instructions to ensure the safe and effective use of this product. Please read this guide thoroughly before installation and use.

General Safety Guidelines

- Ensure that the product is used only in accordance with the manufacturer's instructions.
- Always inspect the product for any signs of damage or wear before use.
- Keep the product out of reach of children and unauthorized users.
- Do not modify or alter the product in any way.
- Be aware of your surroundings and ensure a safe environment when handling firearms.
- Report any unsafe products or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Only use the recoil spring plug with compatible firearms, specifically Government or Commander model pistols.
- Ensure that the firearm is unloaded before installation or maintenance.
- Wear appropriate safety gear, such as safety glasses, when handling the firearm.
- Do not exceed the manufacturer's specifications for the recoil spring plug.
- Use only authorized bushings (EGW Thick Flange, Melt, or Carry Bevel) with this product.
- Be cautious of the weight differences between Solid End and Open End plugs to avoid miscalculations in firearm performance.

Instructions for Installation and Usage

1. Preparation:

- Ensure the firearm is completely unloaded.
- Gather necessary tools for the installation process.

2. Installation:

- Remove the existing recoil spring plug from the firearm.
- Select the appropriate recoil spring plug (Solid End or Open End) based on your guide rod type.
- Align the new recoil spring plug with the recoil spring and guide rod.
- Gently insert the recoil spring plug into the firearm, ensuring a snug fit.

3. Usage:

- After installation, perform a function check to ensure the firearm operates correctly.
- Regularly check the recoil spring plug for signs of wear or damage during maintenance routines.
- If any issues arise during use, discontinue use immediately and consult a qualified gunsmith.

Disposal Instructions

- Dispose of the recoil spring plug in accordance with local regulations.
- If the product is damaged or no longer usable, ensure that it is disposed of safely to prevent any potential

hazards.

Contact Information for Further Support

For any questions or concerns regarding the 1911 Long Nose Recoil Spring Plug, please refer to the manufacturer's website or contact their customer service for assistance. Ensure you have the product details ready for a more efficient response.

By following these guidelines, you can help ensure your safety and the safe operation of your firearm. Thank you for your attention to these important safety instructions.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk