

# DESERT EAGLE (POST 2017) VORTEX VIPER/VENOM SIGHT MOUNT - EGW DESERT EAGLE (POST 2017) VORTEX VIPER/VENOM SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.811" Overall Width: .99" Mounting Hardware: (2) 6-32 Button Head Screws, (2) 6-32 Flat Head Screws, (1) 6-32 Set Screw Red Dot Fitment: Vortex Viper/Venom, Burris FastFire, Crimson Trace CTS-1200, CTS-1300, Docter EGW's red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with our mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight\* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation.



## Attributes

- Name: [EGW DESERT EAGLE \(POST 2017\) VORTEX VIPER/VENOM SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000536
- Mfr. No.: 49297
- Colour: Black
- Material: Aluminum
- Model: Desert Eagle
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Magnum Research
- Delivery weight: 0.154kg
- Shipping height: 13mm
- Shipping width: 89mm
- Shipping length: 140mm
- UPC: 841370116942

## Item details

Made in USA

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for DESERT EAGLE \(POST 2017\) VORTEX VIPER/VENOM SIGHT MOUNT](#)
- [About Us](#)

# Safety Instruction Guide for DESERT EAGLE (POST 2017) VORTEX VIPER/VENOM SIGHT MOUNT

## Introduction

Thank you for choosing the DESERT EAGLE (POST 2017) VORTEX VIPER/VENOM SIGHT MOUNT by EGW. This guide provides essential safety instructions and information to ensure the proper use and installation of your sight mount. Please read the entire guide carefully to understand how to use this product safely and effectively.

## General Safety Guidelines

- Ensure the product is used in accordance with the manufacturer's instructions.
- Always inspect the sight mount and all components before use to ensure they are in good condition.
- Store the sight mount in a safe place, out of reach of children and pets.
- If you experience any issues with the sight mount, discontinue use immediately and seek assistance.
- Report any unsafe products or accidents to the relevant authorities.
- Regularly check for recall updates on the EU's Safety Gate platform.

## Specific Safety Precautions for Use

- Always ensure that the firearm is unloaded before installing or removing the sight mount.
- Use caution when handling tools and mounting hardware to avoid injury.
- Make sure to tighten all screws securely to prevent any movement during use.
- Do not exceed the recommended torque of 15 in/lbs when securing screws.
- Ensure that the red dot sight is properly fitted to the mount before use.
- Avoid placing any foreign objects between the red dot sight and the sight mount other than the recommended paper for easier removal.
- Use blue Loctite on the mounting screws to prevent them from loosening during use.

## Instructions for Installation and Usage

### 1. Remove the Rear Sight

- Ensure the firearm is unloaded.
- Carefully remove the rear sight from your firearm.

### 2. Install the EGW Sight Mount

- Position the EGW Sight Mount in the dovetail of the firearm.
- Ensure it is oriented correctly with the muzzle facing forward.

### 3. Tighten Set Screw (if applicable)

- If your mount includes a set screw, tighten it according to the manufacturer's specifications.

### 4. Place the Red Dot Sight

- Position the red dot sight on the EGW Sight Mount.
- For easier removal, place a small piece of paper between the red dot sight and the sight mount.

### 5. Apply Blue Loctite

- Apply blue Loctite to the provided mounting screws to prevent loosening.

## **6. Torque Mounting Screws**

- Using a 5/64" allen wrench, torque the mounting screws to 15 in/lbs.
- Ensure that:
  - 2 Button Head Cap Screws are used for Vortex Viper and Venom Sights.
  - 2 Flat Head Cap Screws are used for Burris FastFire and Docter Sights.

## **Disposal Instructions**

- Dispose of packaging materials and any unused components responsibly.
- Follow local regulations for disposal of metal and other materials.
- Do not dispose of the product in household waste; check for recycling options.

## **Contact Information for Further Support**

For any questions or further assistance regarding the DESERT EAGLE (POST 2017) VORTEX VIPER/VENOM SIGHT MOUNT, please refer to the manufacturer's website or contact their customer support.

Thank you for your attention to these safety instructions. Your safety is our priority, and we hope you enjoy using your new sight mount responsibly.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)