

CZ SHADOW 2 VORTEX VIPER/VENOM SIGHT MOUNT - EGW CZ SHADOW 2 VORTEX VIPER/VENOM SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.811" Overall Width: .99" Mounting Hardware: (2) 6-32 Button Head Screws, (2) 6-32 Flat Head Screws, (1) 6-32 Set Screw Red Dot Fitment: Vortex Viper/Venom, Burris FastFire, Crimson Trace CTS-1200, CTS-1300, Docter EGW's red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with our mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW CZ SHADOW 2 VORTEX VIPER/VENOM SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000537
- Mfr. No.: 49298
- Colour: Black
- Material: Aluminum
- Model: 75,Shadow,Shadow 2,SP-01 Shadow
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: CZ
- Delivery weight: 0.034kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 133mm
- UPC: 841370116621

Item details

Made in USA

Table of Contents

- Startpage
- CZ Shadow 2 Vortex Viper/Venom Sight Mount Safety Instruction Guide
- About Us

CZ Shadow 2 Vortex Viper/Venom Sight Mount Safety Instruction Guide

Introduction

Thank you for choosing the CZ Shadow 2 Vortex Viper/Venom Sight Mount. This guide provides essential safety instructions, installation procedures, and usage guidelines to ensure your product's safe operation. Please read this guide thoroughly before using the sight mount.

General Safety Guidelines

- **Product Safety:** Ensure safe use of the sight mount by following all instructions. This product is designed for use with specified red dot sights only.
- **Enhanced Recalls:** Stay informed about any product recalls. If this product is recalled, you will be provided with a remedy at no cost.
- **Online Shopping:** If purchased online, ensure that the seller complies with safety requirements equivalent to those of physical stores.
- **Special Consumer Focus:** This product is not intended for use by children. Keep the sight mount and its components out of reach of children.
- **EU Contact Point:** For any safety inquiries, please refer to the manufacturer or retailer from whom you purchased the product.
- **Rapid Alerts:** Monitor the EU's Safety Gate platform for updates on product safety and recalls.

Specific Safety Precautions for Use

- **Installation Safety:** Ensure the firearm is unloaded before installing the sight mount.
- **Tool Safety:** Use the correct tools, specifically a 5/64" allen wrench, to avoid damaging the screws or sight mount.
- **Loctite Application:** Use blue Loctite only on the provided mounting screws to secure them. Avoid contact with the red dot sight to prevent damage.
- **Mounting Orientation:** Install the sight mount from left to right with the muzzle facing forward as specified. Incorrect installation may lead to improper sight alignment.
- **Regular Inspections:** Periodically check the tightness of the mounting screws to ensure they remain secure.

Instructions for Installation and Usage

1. **Remove the Rear Sight:** Ensure the firearm is unloaded. Carefully remove the rear sight from your CZ Shadow 2.
2. **Install the EGW Sight Mount:**
 - Align the EGW Sight Mount in the dovetail.
 - Ensure it is seated properly before proceeding.
3. **Tighten Set Screw:** If applicable, tighten the set screw to secure the mount.
4. **Place the Red Dot Sight:**
 - Position your Vortex Viper/Venom or compatible red dot sight on the EGW Sight Mount.
 - For ease of future removal, place a small piece of paper between the red dot sight and the sight mount.
5. **Apply Blue Loctite:**
 - Apply blue Loctite to the provided mounting screws.
6. **Torque Mounting Screws:**
 - Use a torque wrench to tighten the mounting screws to 15 in/lbs.
 - Ensure that:
 - 2 Button Head Cap Screws are used for Vortex Viper and Venom Sights.

- 2 Flat Head Cap Screws are used for Burris FastFire and Docter Sights.

7. **Final Check:** After installation, doublecheck all screws for tightness and proper alignment.

Disposal Instructions

- Dispose of the sight mount and any packaging materials in accordance with local regulations.
- Do not dispose of electronic components in regular household waste. Check for local recycling programs for electronic waste.

Contact Information for Further Support

For any questions or concerns regarding the CZ Shadow 2 Vortex Viper/Venom Sight Mount, please refer to the manufacturer or retailer from whom you purchased the product. They will provide you with the necessary support and information.

By following these safety instructions, you can ensure a safe and enjoyable experience with your CZ Shadow 2 Vortex Viper/Venom Sight Mount. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk