

WALTHER PPQ M2 LEUPOLD DELTAPOINT PRO SIGHT MOUNT - EGW WALTHER PPQ M2 LEUPOLD DELTAPOINT PRO SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.811" Overall Width: .99" Mounting Hardware: (2) 6-32 Button Head Screws, (2) 6-32 Flat Head Screws, (1) 6-32 Set Screw Red Dot Fitment: Bushnell RXS-100 Crimson Trace CTS-1500 Holosun 407K* Holosun 507K* Holosun EPS-GR* Holosun EPS-RD* Holosun EPS-Carry-GR* Holosun EPS-Carry-RD* Jpoint Leupold Delta Point Pro Optima Redfield Accelerator Shield RMS Shield RMSc Shield SMS Sig Romeo Zero EGW's red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with our mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW WALTHER PPQ M2 LEUPOLD DELTAPOINT PRO SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000543
- Mfr. No.: 49394
- Colour: Black
- Material: Aluminum
- Model: PPQ M2
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Walther
- Delivery weight: 0.227kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 127mm
- UPC: 841370116850

Item details

Made in USA

Table of Contents

- Startpage
- WALTHER PPQ M2 LEUPOLD DELTAPOINT PRO SIGHT MOUNT Safety Instruction Guide
- About Us

WALTHER PPQ M2 LEUPOLD DELTAPOINT PRO SIGHT MOUNT Safety Instruction Guide

Introduction

Thank you for choosing the WALTHER PPQ M2 LEUPOLD DELTAPOINT PRO SIGHT MOUNT. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read and follow all instructions carefully to avoid potential hazards and ensure optimal performance.

General Safety Guidelines

- **Product Safety:** Ensure safe use by following all instructions provided in this guide. This product is designed for use with specific red dot sights and should not be modified.
- **Enhanced Recalls:** Stay informed about any recalls or safety notices through official channels. If you receive a recall notice, cease use immediately and follow the instructions provided.
- **Online Shopping:** When purchasing online, ensure that you are buying from authorized sellers who comply with safety regulations.
- **Special Consumer Focus:** Keep this product out of reach of children. It contains small parts that could pose a choking hazard.
- **EU Contact Point:** For any safety inquiries, please refer to the contact information provided by the retailer or manufacturer.
- **Rapid Alerts:** Regularly check the EU's Safety Gate platform for updates on unsafe products.

Specific Safety Precautions for Use

- **Installation Safety:**
 - Ensure the firearm is unloaded before starting the installation process.
 - Use only the provided mounting hardware to ensure a secure fit.
- **Handling:**
 - Always treat the firearm as if it is loaded, even when it is not.
 - Keep your fingers off the trigger until you are ready to shoot.
- **Use of Red Dot Sight:**
 - Ensure that the red dot sight is securely mounted before use.
 - Do not use the sight if it is damaged or malfunctioning.
- **Personal Protective Equipment:**
 - Wear appropriate eye protection when handling firearms.
 - Consider using hearing protection when shooting.

Instructions for Installation and Usage

1. **Remove the Rear Sight:**
 - Use an appropriate tool to carefully remove the rear sight from your firearm.
2. **Install the EGW Sight Mount:**
 - Align the EGW Sight Mount in the dovetail.
 - Ensure it is placed from left to right with the muzzle facing forward.
3. **Tighten Set Screw (if applicable):**
 - Use a 5/64" allen wrench to tighten the set screw securely.
4. **Place the Red Dot Sight:**
 - Position the red dot sight on the EGW Sight Mount.
 - To facilitate easier removal, place a small piece of paper between the red dot sight and the mount.
5. **Apply Blue Loctite:**
 - Apply blue Loctite to the provided mounting screws to secure them.
6. **Torque Mounting Screws:**

- Use a torque wrench to tighten the mounting screws to 15 in/lbs.

7. Screw Types:

- 2 Button Head Cap Screws Provided for Vortex Viper and Venom Sights.
- 2 Flat Head Cap Screws Provided for Burris FastFire and Docter Sights.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the product reaches its end of life, dispose of it in a way that complies with local waste disposal regulations. Consider recycling where possible.

Contact Information for Further Support

For any questions or concerns regarding the WALTHER PPQ M2 LEUPOLD DELTAPOINT PRO SIGHT MOUNT, please refer to the contact information provided by the retailer or manufacturer. Ensure you have your purchase details and product information ready for any inquiries.

By adhering to these guidelines, you can ensure the safe and effective use of your WALTHER PPQ M2 LEUPOLD DELTAPOINT PRO SIGHT MOUNT. Thank you for prioritizing safety and compliance.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk