

SIG SAUER P210A LEUPOLD DELTAPOINT PRO SIGHT MOUNT - EGW

SIG P210A LEUPOLD DELTAPOINT PRO SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.811" Overall Width: .99" Mounting Hardware: (2) 6-32 Button Head Screws, (2) 6-32 Flat Head Screws, (1) 6-32 Set Screw Red Dot Fitment: Vortex Viper/Venom, Burris FastFire, Crimson Trace CTS-1200, CTS-1300, Docter EGW's red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with our mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW SIG P210A LEUPOLD DELTAPOINT PRO SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000547
- Mfr. No.: 49398
- Colour: Black
- Material: Aluminum
- Model: P210A
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Sig Sauer
- Delivery weight: 0.033kg
- Shipping height: 25mm
- Shipping width: 89mm
- Shipping length: 140mm
- UPC: 841370116669

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for SIG SAUER P210A LEUPOLD DELTAPOINT PRO SIGHT MOUNT
- About Us

Safety Instruction Guide for SIG SAUER P210A LEUPOLD DELTAPOINT PRO SIGHT MOUNT

Introduction

Thank you for choosing the SIG SAUER P210A LEUPOLD DELTAPOINT PRO SIGHT MOUNT. This guide provides essential safety instructions and installation procedures to ensure the safe and effective use of this product. Please read and follow these instructions carefully to maximize safety and performance.

General Safety Guidelines

- **Product Safety:** Ensure safe handling and use of the sight mount. Familiarize yourself with its features and functions before use.
- **Enhanced Recalls:** Be aware of the process for product recalls. If notified, follow the provided instructions to return or remedy the product.
- **Online Shopping:** If purchased online, ensure that the platform complies with safety standards similar to physical stores.
- **Special Consumer Focus:** This product is not intended for use by children. Ensure that it is stored out of reach to prevent accidental use.
- **EU Contact Point:** For any safety inquiries, please refer to the contact information provided by your retailer.
- **Rapid Alerts:** Stay updated on any safety alerts regarding this product through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Hazard Identification:**
 - Improper installation can lead to malfunction or accidents.
 - Ensure that the mount is compatible with your red dot sight.
- **Avoiding Hazards:**
 - Always follow installation instructions carefully.
 - Do not modify the mount or the firearm.
 - Regularly check the mount for any signs of wear or damage.
- **Age Specific Warnings:**
 - This product is intended for use by adults only. Keep out of reach of children.

Instructions for Installation and Usage

1. **Remove the Rear Sight:**
 - Carefully take off the rear sight from your firearm.
2. **Install the EGW Sight Mount:**
 - Place the EGW Sight Mount into the dovetail.
3. **Tighten Set Screw:**
 - If applicable, tighten the set screw to secure the mount.
4. **Place the Red Dot Sight:**
 - Position your red dot sight on the EGW Sight Mount.
 - For easier removal, place a small piece of paper between the red dot sight and the mount to prevent Loctite from adhering to the sight.
5. **Apply Blue Loctite:**
 - Use blue Loctite on the provided mounting screws to ensure they remain secure.
6. **Torque Mounting Screws:**
 - Tighten the mounting screws to 15 in/lbs.
7. **Use Appropriate Screws:**

- Use the 2 Button Head Cap Screws for Vortex Viper and Venom sights.
- Use the 2 Flat Head Cap Screws for Burris FastFire and Docter sights.

8. Tool Requirement:

- A 5/64" allen wrench is required for installation.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Ensure that any packaging materials are also disposed of responsibly.
- Do not dispose of the product in regular household waste.

Contact Information for Further Support

For further assistance or inquiries regarding the SIG SAUER P210A LEUPOLD DELTAPOINT PRO SIGHT MOUNT, please consult the retailer from whom you purchased the product.

By following these safety instructions and guidelines, you can ensure a safe and effective experience with your SIG SAUER P210A LEUPOLD DELTAPOINT PRO SIGHT MOUNT. Thank you for your attention to safety!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk